





LMTM 1

Description	2-way 4th-order vented-box system
Drive units	1x 125mm (5in) in bass/mid 1x 25mm (1in) in high-frequency
Frequency range	-6dB at 65Hz and 22kHz
Frequency response	75Hz – 20kHz \pm 3dB on reference axis
Dispersion	Within 2dB of response on reference axis Horizontal: over 40° arc Vertical: over 10° arc
Sensitivity	91dB spl (2.83V, 1m)
Harmonic distortion	2nd & 3rd harmonics <1% 100Hz – 15kHz (90dB spl, 1m)
Nominal impedance	8 Ω
Crossover frequency	3.5kHz
Recommended amplifier power	25W – 100W continuous into 8 Ω on unclipped programme.
Max. Recommended Cable impedance	0.2 Ω
Dimensions	Height: 280mm (11in) Width: 140mm (5.5in) Depth: 191mm (7.5in)
Net weight	2.4kg (5.3 lb)
Finishes	White and various colour finishes



L I S T E N A N D Y O U ' L L S E E

B&W Loudspeakers Ltd, Meadow Road, Worthing, BN11 2RX, England Tel: +44 (0) 1903 524801 Fax: +44 (0) 1903 524725.
 B&W Loudspeakers of America, 54 Concord Street, North Reading, MA 01864-2699 Tel: (1978) 664 2870 Fax: (1978) 664 4109.
 B&W Loudspeakers (Asia) Ltd, Flat U, 11F Camelpaint, Building Block 111, 60 Hoi Yuen Road, Kwun Tong, Kowloon, Hong Kong.
 Tel: (8522) 790 8903 Fax: (8522) 341 2777. Copyright © B&W Loudspeakers Ltd. Printed in England.
 B&W Loudspeakers Ltd reserves the right to amend details of the specifications without notice in line with technical developments.
<http://www.bwspeakers.com>