



DKT-M - DIGITAL AUDIO MINIATURE FOIL SCREENED SOLID CONDUCTOR TWIN CABLE

This is a miniature solid conductor cable, similar in construction to KST-M, but true 110 ohm, specifically for use with Krone and other IDC type wiring systems. Cores and drain wire are all solid conductor, 0.37mm diameter. To keep the overall diameter to a minimum, the drain is a bare solid wire. The foil screen is bonded to the outer PVC jacket, as with DFT, FST and KST-M.

Technical Specification:

Conductor:	1/0.37mm (0.107mm ²) tinned copper wire
Insulation:	Foamed polypropylene, OD 1.00mm, red, black
Drain:	1/0.37mm (0.107mm ²) tinned copper wire
Screen:	Bondable aluminium/polyester tape
Jacket:	PVC, OD 2.90mm
Impedance:	110 ±10 ohms
Capacitance:	41 pF/m
Max. conductor resistance:	170 ohms/km
Weight:	0.9kg/100m
Reel lengths:	500m
Cut lengths:	Available in any multiple of 1 metre

31-986 CANFORD DKT-M CABLE 1 pair, Turquoise

UK Sales - tel 0191 418 1122
fax 0191 418 1123
sales@canford.co.uk

International Sales - tel +44 191 418 1133
fax +44 191 418 1134
international@canford.co.uk

Tech Support - tel 0191 418 1144
fax 0191 418 1145
techsupport@canford.co.uk