



KST-M - MINIATURE FOIL SCREENED SOLID CONDUCTOR TWIN CABLE

This is a miniature solid-conductor twin screened cable, specifically for use with Krone 10 pair blocks. Cores and drain wire are all solid conductor, 0.5mm diameter, however this differs from KST cable in that, to keep the overall diameter to an absolute minimum, the drain wire does not have a conductive plastic jacket. The foil screen is bonded to the outer PVC jacket, as with KST and FST.

Technical Specification:

Conductors:	1/0.37mm (0.107mm ²) tinned copper wire
Insulation:	PVC, brown, white
Drain:	1/0.37mm (0.107mm ²) tinned copper wire
Screen:	Bondable AL/Polyester tape
Jacket:	PVC, OD 2.2mm ±5%
Capacitance:	110pF/metre core to core, 210pF/metre core to core +screen
Max conductor resistance:	170 ohms/km
Reel lengths:	500 metres
Weight:	3.5kg/500m drum
Cut lengths:	Available in any multiple of 1 metre, minimum 10 metres

FST is a Canford registered trademark.

31-083 CANFORD KST-M CABLE 1 pair, Orange

UK Sales - tel 0191 418 1122
fax 0191 418 1123
sales@canford.co.uk

International Sales - tel +44 191 418 1133
fax +44 191 418 1134
international@canford.co.uk

Tech Support - tel 0191 418 1144
fax 0191 418 1145
techsupport@canford.co.uk