

BARTOLUCCI DOUBLE C CORE TRANSFORMERS



BARTOLUCCI GIUSEPPE
VIA SAN MARTINO , 3
61032 FANO (PU)
Tel.0721 861238 - 334 3863576



info@giuseppebartolucci.com

www.giuseppebartolucci.com

SINGLE ENDED TRANSFORMER MODEL **CFCUF5**

S.E. cuffie "C" CORE

DATA 14/02/2013

TECHNICAL SPECIFICATIONS

TESTED *Giuseppe Bartolucci*

NOMINAL POWER rms	WATTS	5,5
PRIMARY IMPEDANCE	OHMS	5000
SECONDARY IMPEDANCE	OHMS	32 - 300
PRIMARY INDUCTANCE	Hy.	45
PRIMARY RESISTANCE	OHMS	358
PRIMARY CURRENT	mA.	45
FREQUENCY RESPONSE	-3db	4Hz/90K
POTTED	YES	YES
CAN TYPE	STEEL	STEEL
SIZE	mm.	M.3
WEIGHT	KILOS	3,5

PRIMARY CONNECTIONS 5000 OHMS
USE SILI RED "0" AND SILI RED FOR 5000 OHMS

SECONDARY CONNECTIONS
CHOISE YELLOW 0 - WHITE 32 - GREY 300

SEONDARY RDC Ohms 0 - 3,8 - 28

PRICE EUROS 230,00 ONE PIECE