

	With Bucking Magnet		
	M&K 1	M&K 2	Average
Fs	50.89	49.032	49.96 Hz
Qms	4.344	4.143	4.24
Vas	14.11	15.848	14.98 L
Cms	0.217	0.243405	0.23 mm/N
Mms	45.12	43.287	44.20 g
Rms	3.321	3.219	3.27 kg/s
Sd	214.08	214.08	214.08 cm^2
Qes	0.947	0.896722	0.92
Re	3.76	3.774	3.77 ohms
Le	0.79	0.765578	0.78 mH
Z	7.70	7.594	7.65 ohms
BL	7.57	7.492	7.53 Tm
Qts	0.777	0.737173	0.76
no	0.18	0.195744	0.19 %
1-W SPL	84.68	84.935	84.81 dB
2.83V SPL	87.96	88.198	88.08 dB

	Without Bucking Magnet		
	M&K 1	M&K 2	Average
Fs	50.524	48.913	49.72 Hz
Qms	4.467	4.125	4.30
Vas	14.822	16.734	15.78 L
Cms	0.227658	0.257014	0.24 mm/N
Mms	43.588	41.194	42.39 g
Rms	3.098	3.069	3.08 kg/s
Sd	214.08	214.08	214.08 cm^2
Qes	1.095	1.007	1.05
Re	3.775	3.778	3.78 ohms
Le	0.828632	0.801095	0.81 mH
Z	7.93	7.786	7.86 ohms
BL	6.908	6.891	6.90 Tm
Qts	0.879224	0.80952	0.84
no	0.164081	0.182688	0.17 %
1-W SPL	84.169	84.635	84.40 dB
2.83V SPL	87.43	87.893	87.66 dB