


Magnecraft
191 Waukegan Rd, Ste 206
Northfield, IL 60093-2743
Phone: (847)441-2526
Fax: (847)441-2522
Email: relays@magnecraft.com

Item # W199AX-9, 199 Open Style Power Relays / DPST-NO, 40 Amp Rating (AC)
QUOTE

199 Open Style Power Relays / DPST-NO, 40 Amp Rating (AC)



[CONTACT CHARACTERISTICS](#) · [SPECIFICATIONS](#) · [COIL CHARACTERISTICS](#) · [PERFORMANCE CHARACTERISTICS](#) · [ENVIRONMENT](#) · [PRODUCT CERTIFICATIONS](#)

CONTACT CHARACTERISTICS

Contact Rating	40 A
Contact Configuration	DPST-NO
Contact Materials	Silver Alloy
Maximum Switching Voltage	600 V
Switching Current at Voltage (AC, Resistive)	40 A at 277 V 50 / 60 Hz
Switching Current at Voltage (DC, Resistive)	40 A at 28 VDC
Switching Current at Voltage (Pilot Duty)	A600
Minimum Switching Requirement	1 A at 12 VAC

SPECIFICATIONS

Nominal Input Voltage	120 VAC 50/60 Hz
Coil Resistance	290 Ohm
Cover Style	Open Style
Weight	227 to 312 G

COIL CHARACTERISTICS

Operating Range - % of Nominal (AC)	85 to 110 %
Operating Range - % of Nominal (DC)	80 to 110 %
Average Consumption (AC)	10 VA
Average Consumption (DC)	4 W
Drop-out Voltage Threshold (DC)	10 %
Drop-out Voltage Threshold (AC)	10 %

PERFORMANCE CHARACTERISTICS

Electrical Life (UL508), Operations at Rated Current (Resistive)	100000
Mechanical Life, Unpowered	1000000
Operating Time (Response Time)	30 ms

ENVIRONMENT

Ambient Air Temperature around the Device - Storage	-40 to +85 °C
Ambient Air Temperature around the Device - Operation	-40 to +55 °C
Connection	8 AWG 10 mm ²
Terminal Tightening Torque	7 to 9 in lb 0.8 to 1.0 N·m

PRODUCT CERTIFICATIONS

Agency Approvals	UL CE CSA
------------------	-----------------
