

LOW-NOISE DUAL OPERATIONAL AMPLIFIER


■ GENERAL DESCRIPTION

The NJM2041 is a bipolar operational amplifier which is designed as low noise version of the NJM4558 with high output current and fast slew rate ($3V/\mu s$) and wide unity gain bandwidth (7MHz) constructed using New JRC Planar epitaxial process.


■ FEATURES

- Operating Voltage ($\pm 4V \sim \pm 22V$)
- High Output Current (25mA.)
- Slew Rate ($3V/\mu s$ typ.)
- Unity Gain Bandwidth (7MHz typ.)
- Package Outline DIP8, DMP8, SIP8
- Bipolar Technology

■ PACKAGE OUTLINE



■ PIN CONFIGURATION




PIN FUNCTION

1. A OUTPUT
2. A-INPUT
3. A+INPUT
4. V⁻
5. B+INPUT
6. B-INPUT
7. B OUTPUT
8. V⁺

4

■ EQUIVALENT CIRCUIT (1/2 Shown)



NJM2041

■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V ⁺ /V ⁻	±22	V
Differential Input Voltage	V _{ID}	±30	V
Input Voltage	V _{IC}	±15 (note)	V
Power Dissipation	P _D	(DIP8) 500 (DIM8) 300 (SIP8) 800	mW
Operating Temperature Range	T _{opr}	-20~+75	°C
Storage Temperature Range	T _{stg}	-40~+125	°C

(note) For supply voltage less than ±15V, the absolute maximum input voltage is equal to the supply voltage.

■ ELECTRICAL CHARACTERISTICS

(Ta =25°C, V⁺/V⁻ =±15V)


PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Input Offset Voltage	V _{IO}	R _S ≤10kΩ	—	0.3	3	mV
Input Offset Current	I _{IO}		—	10	200	nA
Input Bias Current	I _B		—	200	500	nA
Input Resistance	R _{IN}		50	200	—	kΩ
Large signal Voltage Gain	A _V	R _L ≥2kΩ, V _O =±10V	86	110	—	dB
Maximum Output Voltage Swing 1	V _{OM1}	R _L ≥10kΩ	±12	±14	—	V
Maximum Output Voltage Swing 2	V _{OM2}	I _O =25mA	±10	±11.5	—	V
Input Common Mode Voltage Range	V _{ICM}		±12	±14	—	V
Common Mode Rejection Ratio	CMR	R _S ≤10kΩ	70	100	—	dB
Supply Voltage Rejection Ratio	SVR	R _S ≤10kΩ	76	100	—	dB
Operating Current	I _{CC}		—	6	8	mA
Slew Rate	SR		—	3	—	V/μs
Gain Bandwidth Product	GB		—	7	—	MHz
Equivalent Input Noise Voltage	V _{NI}	FLAT+JISA R _S =300Ω	—	0.48	0.61	μVRms

(note) : New JRC's general selected products D-rank are also prepared for the noise standard (R_S=2.2kΩ, RIAA, V_{NI}=1.4μV Max.)

■ TYPICAL CHARACTERISTICS


Lage Signal Voltage Gain
vs. Frequency

($V^+/V^- = \pm 15V$, $R_L = 2k\Omega$, $T_a = 25^\circ C$)




Equivalent Input Noise Voltage

($V^+/V^- = \pm 15V$, $T_a = 25^\circ C$)




Maximum Output Voltage Swing
vs. Load Resistance

($V^+/V^- = \pm 15V$, $T_a = 25^\circ C$)




Maximum Output Voltage Swing
vs. Output Current

($T_a = 25^\circ C$)




Operating Current vs. Temperature

($V^+/V^- = \pm 15V$)





Maximum Output Voltage Swing
vs. Temperature

($V^+/V^- = \pm 15V$, $R_L = 10k\Omega$)



■ TYPICAL CHARACTERISTICS



4

