


# F SERIES

# W4-1337SA



4" TI FULL RANGE

- FULL RANGE FREQUENCY RESPONSE**

- HIGH POWER LOADING DESIGN**

- DIE CAST BASKET, TITANIUM COLOR PAINTED, VC VENTED DESIGN**

- TITANIUM CONE WITH SANTOPRENE SURROUND**

- MAGNETICALLY SHIELDED**

- NEODYMIUM DESIGN, UNDERHUNG MOTOR DESIGN**

- LOW 2nd, 3rd DISTORTION DESIGN**

DIAPHRAGM MTL	Titanium
SURROUND MTL	Rubber
NOMINAL IMPEDANCE	8 Ω
DCR IMPEDANCE	6.8 Ω
SENSITIVITY 1W/1m	87 dB
FREQUENCY RESPONSE	70-20K Hz
FREE AIR RESONANCE	70 Hz
VOICE COIL DIAMETER	25.4 mm
AIR GAP HEIGHT	10 mm
RATED POWER INPUT	25 W
MAXIMUM POWER INPUT	50 W
FORCE FACTOR, BL	5.37 TM
MAGNET WEIGHT (oz)	Neodymium
MOVING MASS	4.61 g
FERRO FLUID ENHANCED	No
SUSPENSION COMPL.	1053MN <sup>-1</sup>
EFFEC.PISTON AREA	0.0057M <sup>2</sup>
Levc	0.015mH
Zo	28ohm
X-max	3 mm
Vas	4.86 Litr.
Qts	0.37





VOICE:886.2.26570282 FAX:886.2.26580166  
E-MAIL :info@tb-speaker.com

Qms

1.51

Qes

0.49

---

**CLOSE**