



Licron®

Permanent Static Dissipative Coating

1755

Introduction

Licron® is a revolutionary and innovative concept in permanent static dissipative coatings. It provides excellent adhesion to metals, plastics, paints and most other surfaces. Licron® operates from 0-100% humidity. The cured coating is durable, will not chip and maintains 10⁶-10⁸ ohms resistivity. Licron® is translucent, and can be used on any surfaces requiring a translucent coating.

- Features / Benefits
- Translucent Conductive Coating
 - Permanently Static Dissipative
 - Surface Resistivity of 10⁶-10⁸ ohms
 - Humidity Independent
 - Superior Adhesion

Chemical Components

Acetoxyethane.....	(141-78-6)	40-60%
2-propanol.....	(67-63-0)	10-20%
Acrylic Copolymer		2-4%
Dipropylene glycol monomethyl ether.....	(34590-94-8)	3-6%
1-Methoxy-2-propyl acetate.....	(108-65-6)	<<0.1%
Stoddard Solvent.....	(8052-41-3)	<0.2%
Tin Oxide.....	(18282-10-5)	8-10%
Propane.....	(74-98-6)	10-15%
Butane.....	(106-97-8)	5-10%

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

Licron® is available in the following sizes:

- 1755-10S 10 Ounce Aerosol

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America
Tech Spray L.P.
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

Europe
Techspray International
UNIT 4, 44/46 Bunyan Road, Kempston
Bedford MK42 8HL United Kingdom
+44 (0) 1234 855443
email: tseurope@techspray.com

Countries Outside US
Call to locate a distributor
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P.
P.O. Box 949
Amarillo, TX 79105
www.techspray.com

[English MSDS](#)
[French MSDS](#)
[German MSDS](#)
[Italian MSDS](#)
[Spanish MSDS](#)

