



DATA SHEET FOR
TRANSFORMER # Q-4009172-B

Made for VIKTOR STOLBOVOY

LEADS		SCHEMATIC				LEADS
S#16/8"	0V	WHITE		BROWN	0V	S#12/8"
S#16/8"	120V	YELLOW		BROWN	38V RMS / 12A RMS	S#12/8"
S#16/8"	0V	ORANGE		ORANGE	0V	S#12/8"
S#16/8"	120V	BLACK		ORANGE	38V RMS / 12A RMS	S#12/8"
				BLUE	0V	S#12/8"
				BLUE	10V RMS / 12A RMS	S#12/8"
				GRAY	0V	S#12/8"
				GRAY	10V RMS / 12A RMS	S#12/8"
				GRN/YEL	STATIC SHIELD	S#18/8"

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120/240V +/-10%
RATED PRIMARY CURRENT: 10.0/5.0A
RATED FREQUENCY: 50/60 Hz
TEMP. RISE AT RATED LOAD: 60 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 6.4"	POTTED CENTER	CORE # 901300
H = 3.6"	FLAT BOTTOM	CORE LOSS = 6.1 W
WEIGHT = 20 LBS.	HOLE DIAMETER = 3/8"	NO-LOAD CURRENT = 55 mA

Dimensions stated above are nominal. Tolerance is 10%.

MAGNETIC SHIELD = 70mm
OTHER SPECIFICATIONS: Transformer meets UL 506, EN 61558 and CSA C22.2 No. 66 standards.
Class B insulation.

Label: Transformer # Q-4009172-B
SPEC DATE: 03/04/08 Made for VIKTOR STOLBOVOY
(Logo) P/N

By: **MX**

(date code)

TOROID CORPORATION of MD