



# DE980TN

## HF Drivers - 1.4 Inches

220 W continuous program power capacity  
 1.4" horn throat diameter  
 75 mm (3 in) CCAW voice coil  
 Titanium diaphragm  
 500 - 18000 Hz response  
 108 dB sensitivity  
 Neodymium magnet assembly with shorting copper cap

### Specification

Throat Diameter	36 mm (1.4 in)
Nominal Impedance	8 ohm
Minimum Impedance	8.1 ohm
Continuous Power Handling	220 W
Nominal Power Handling (AES)	110 W
Sensitivity (1W/1m)	108 dB
Frequency Range	0.5 - 18 kHz
Recommended Crossover	1.2 kHz
Voice Coil Diameter	75 mm (3 in)
Winding Material	Aluminium
Inductance	0.14 mH
Diaphragm material	Titanium
Flux Density	2.05 T
Magnet Material	Neodymium Ring

### Mounting & Shipping

Shipping Box (4 units)	300x160x180 mm (11.8x6.3x7.1 in)
Replacement Diaphragm	TBA

### Mounting & Shipping

Overall Diameter	131 mm (5.2 in)
Depth	52 mm (2 in)
Net Weight	2.5 kg (5.5 lb)
Shipping Weight (4 units)	10.6 kg (23.4 lb)