

Goto speaker drivers



SG-30WS



SG-38WN

30cm Woofer	SG-30W	SG-30WS
Nominal Diameter	30cm	30cm
Maximum Input Power (Music)	35w	35w
Impedence (Ohms)	8-16	8-16
Efficiency	100db/w/m	100db/w/m
Frequency Response	36Hz - 1.5 KHz	36Hz - 1.5 KHz
Total Magnetic Flux (Maxwell)	1,000,000	1,300,000
Magnetic Flux Density (Gauss)	16,000	17,000
Crossover frequency	200 - 1500 Hz	200 - 1500 Hz
Fs	36 Hz (Qts 0.25)	36 Hz (Qts 0.25)
Dimensions (mm)	345d x 144	345d x 169
Magnet Dimensions (mm)	168d x 74	168d x 99

38cm Woofer	SG-38WN	SG-38WNS	SG-38WNSS	SG-38WNSP	SG-38WNSSP
Nominal Diameter	38cm	38cm	38cm	38cm	38cm
Maximum Input Power (Music)	40w	40w	40w	40w	40w
Impedence (Ohms)	5-16	5-16	5-16	5-16	5-16
Efficiency	105db/w/m	108db/w/m	110db/w/m	110db/w/m	110db/w/m
Frequency Response	28Hz - 800 KHz	28Hz - 800 KHz	28Hz - 800 KHz	28Hz - 800 KHz	28Hz - 800 KHz
Total Magnetic Flux (Maxwell)	1,300,000	1,600,000	3,000,000	2,200,000	3,000,000
Magnetic Flux Density (Gauss)	16,000	18,000	18,000	20,000	20,000
Crossover frequency	200 - 500 Hz	200 - 500 Hz	200 - 500 Hz	200 - 500 Hz	200 - 500 Hz
Fs	28 Hz	28 Hz	28 Hz	28 Hz	28 Hz
Qts	0.25	0.25	0.25	0.25	0.25
Dimensions (mm)	435d x 165	435d x 191	435d x 216	435d x 191	435d x 216
Magnet Dimensions (mm)	200d x 76	202d x 102	202d x 127	220d x 102	220d x 127