



Notes!
 Components designated 1xx are placed on main PCB
 Components designated 2xx are placed on heatsink or speaker binding posts
 Components designated 3xx are additional output protection circuit
 All capacitors 100V except where designated otherwise
 Q111 must be placed on main heatsink
 Q109 and Q110 must be fitted with suitable heatsink
 V-I Limiter: 1: (R303/R304/Rxxx) = app. 100R for safe SOA

Copyright		DELTA AUDIO DENMARK www.delta-audio.com		Krell-Close KSA-50 Clone		Krell-Close KSA-50 Clone		Krell-Close KSA-50 Clone	
Rev.	Date	Rev.	Date	Rev.	Date	Rev.	Date	Rev.	Date
1.1	17.10.2004	1.1	21.10.2004	1.1	21.10.2004	1.1	21.10.2004	1.1	21.10.2004
1.2		1.2		1.2		1.2		1.2	
1.3		1.3		1.3		1.3		1.3	
1.4		1.4		1.4		1.4		1.4	
Project	JD	Design	JD	Design	JD	Design	JD	Design	JD
Author	UR	Author	UR	Author	UR	Author	UR	Author	UR
Size	A3	Size	A3	Size	A3	Size	A3	Size	A3
Sheet	1 of 1	Sheet	1 of 1	Sheet	1 of 1	Sheet	1 of 1	Sheet	1 of 1



