Dual Voice Coil Parameter guide														
												Rs=	4	
Coils Parallel				Coils Series				Single Coil (other open)				Resistive Damped		
Fs	24.0	Hz		Fs	24.0	Hz		Fs	24.0	Hz		Fs	24.0	Hz
Qts	0.380			Qts	0.380			Qts	0.724			Qts	0.507	
Qes	0.400			Qes	0.400			Qes	0.800			Qes	0.800	
Vas	93.0	liters		Vas	93.0	liters		Vas	93.0	liters		Vas	93.0	liters
Re	1.80	Ohms		Re	7.2	Ohms		Re	3.6	Ohms		Re	3.6	Ohms
Dia	26.2	cm		Dia	26.2	cm		Dia	26.2	cm		Dia	26.2	cm
Xmax	13.5	mm		Xmax	13.5	mm		Xmax	13.5	mm		Xmax	13.5	mm
Pe_max	1000.0	Watts		Pe_max	1000	Watts		Pe_max	500	Watts		Pe_max	500	Watts
Le	0.00200	Henrys		Le	0.004	Henrys		Le	0.002	Henrys		Le	0.002	Henrys
Qms	7.60			Qms	7.60			Qms	7.60			Qms	1.38	
Sd	0.0539	m^2		Sd	0.0539	m^2		Sd	0.0539	m^2		Sd	0.0539	m^2
Mmd	0.1930	kg		Mmd	0.1930	kg		Mmd	0.1930	kg		Mmd	0.1930	kg
Cms	0	m/N		Cms	0	m/N		Cms	0.000228	m/N		Cms	0.000228	m/N
Bl	11.45	Tesla*m		Bl	22.89	Tesla*m		Bl	11.45	Tesla*m		Bl	11.45	Tesla*m
Rms	3.83	kg/s		Rms	3.83	kg/s		Rms	3.83	kg/s		Rms	21.07	kg/s
no	93.40	dB/2.83V		no	87.38	dB/2.83V		no	87.38	dB/2.83V		no	87.38	dB/2.83V
no	86.92	dB/1W		no	86.92	dB/1W		no	83.91	dB/1W		no	83.91	dB/1W