

3M Model 6100 Projection Panel

Your basic tool for computer-based presentations

Bring your computer presentations to life with the 3M Model 6100 Projection Panel. Very affordable, it is still loaded with state-of-the-art features including a 16.7-million color palette, Active-Matrix TFT technology and a 10.4-inch diagonal display for truer, more vibrant colors. It also features a VirtualMouse remote that becomes a wireless mouse, letting you control your presentations from almost anywhere in the room. And the six unique Presentation Tools let you reveal, blank, freeze, time, magnify and point to your images on the screen. The Model 6100 is easy to set up and — with its slim, lightweight design — easy to carry around.

Key Features

- 16.7 million colors
- Large 10.4" LCD display with 6-bit TFT glass
- 640 x 480 VGA resolution
- Supports SVGA 800 x 600 resolution
- VirtualMouse remote control
- Six built-in presentation tools
- Automated image optimization
- Front or rear projection
- Multilingual on-screen menu system

Computer Compatibility

- IBM® and compatibles with SVGA (compressed to 640 x 480, 256-color mode), VGA
- Apple® Macintosh® up to 832 x 624 resolution
- Prestored Modes: VESA 640 x 480, VESA 800 x 600 and Quadra 832 x 624 (compressed to 640 x 480, 256-color mode)
- Three user-programmable modes for computer graphics cards with nonstandard timing

Presentation Tools

- Six function keys: F1: Reveal, F2: Blank, F3: Freeze, F4: Timer, F5: Magnification, F6: Pointer

Included:

- VGA video cable
- Serial mouse cable, with parallel adapter and PS2 mouse adapter
- Remote control unit
- Power supply and cord
- Multilingual Operator Reference Guide

Accessories:

- Macintosh cable set, including VirtualMouse Mac adapter
- Carry case

*Macintosh, Mac and Quadra are trademarks of Apple Computer, Inc.
IBM is a trademark of International Business Machines Corporation
Microsoft is a trademark of Microsoft Corporation*

Technical Specifications

LCD Type: Active-Matrix Thin Film Transistor (TFT)

Active Display Area: 8.3" x 6.2" (211 mm x 152 mm)

Resolution: 640 x 480

Colors: 16.7 million

Contrast Ratio: 100:1 typical

Response Time: 30 ms typical

Panel Dimensions: 14.2" x 12.8" x 2.3"
(355 mm x 320 mm x 58 mm)

Weight: 2.5 kg (5.5 lbs)

Operating Temperature: Maximum 60°C
(140°F) on projector stage

Storage Temperature: -10° to 60°C (14° to 140°F)

Power Supply: Universal (100-250V, 50/60 Hz)
with detachable cord

Regulatory Approvals: FCC Part 15, Subpart B


Warranty: One-year limited warranty on parts and labor

Order Number: XX-0034-1748-0

*Specifications subject to change
without notice.*



We're easy to reach



800-328-1371



<http://www.mmm.com/presentations>
e-mail: presentations@mmm.com

3M Austin Center
Building A145-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000

3M Canada
P.O. Box 5757
London, Ontario, Canada
N6A 4T1

3M Mexico, S.A. de C.V.
Apartado Postal 14-139
Mexico, D.F. 07070
Mexico

Let us help you make the most of your next presentation. We offer everything from presentation supplies to tips for better meetings. And we're the only transparency manufacturer that offers a recycling program for your used transparencies. For late-breaking news, handy references and free product samples, call us toll-free in the continental United States and Canada, 7:30 a.m. to 5:30 p.m. (CST). Or visit our Internet Web site.



Printed on 50% recycled wastepaper,
including 10% post-consumer wastepaper

Litho in U.S.A. © 3M 1996
78-6970-7609-5 (06615.0)LP