


2SK79 Datasheet

絶対最大定格 Absolute Maximum Ratings ($T_a=25^\circ\text{C}$)

Characteristics	Symbol	2SK79
Drain-to-Gate Voltage	V_{DGO}	120V
Source-to-Gate Voltage	V_{SGO}	10V
Drain Current	I_D	200mA
Gate Current	I_G	20mA
Total Power Dissipation	P_T	750mW
Junction Temperature	T_j	120°C
Storage Temperature	T_{stg}	-50 ~ +150°C

電気的特性 Electrical Characteristics ($T_a=25^\circ\text{C}$)


Characteristics	Symbol	Condition	Min.	Typ.	Max.	Unit
Drain-to-Gate Voltage	V_{DGO}	$I_D = 0.1\text{mA}$	120			V
Source-to-Gate Voltage	V_{SGO}	$I_S = 0.1\text{mA}$	10			V
Drain Cutoff Current	I_{DGO}	$V_{DG} = 50\text{V}, I_S = 0\text{A}$			200	nA
Gate Cutoff Current	I_{GSS}	$V_{GS} = 6\text{V}, V_{DS} = 0\text{A}$			200	nA
Drain-to-Source On State Voltage	$V_{DS(on)}$	$V_{DS} = 0.3\text{V}, I_D = 7\text{mA}$			10	V
Pinch-off Voltage	V_p	$V_{DS} = 100\text{V}, I_D = 300\mu\text{A}$		-4.5	-9.5	V
Voltage Amplification Ratio	μ	$V_{DS} = 50\text{V}, I_D = 4\text{mA}, f = 1\text{kHz}$	15	30		
Forward Transfer Conductance	g_m	$V_{DS} = 50\text{V}, I_D = 4\text{mA}, f = 1\text{kHz}$		14		mS
Input Capacitance	C_{ip}	$V_{DS} = 50\text{V}, I_D = 4\text{mA}, f = 1\text{MHz}$		16		pF
Output Capacitance	C_o	$V_{DS} = 50\text{V}, I_D = 4\text{mA}, f = 1\text{MHz}$		2		kΩ
Junction-to-Ambient Thermal Resistance	θ_{j-a}				4	pF
Noise Figure	NF	$V_{DS} = 50\text{V}, I_D = 4\text{mA}, R_g = 500\text{k}\Omega, f = 10\text{Hz}$			126	°C/W
					30	dB



- 1. S
- 2. D
- 3. G

[第1表] 2SK79 の最大定格と電気的特性

2022 J



[第19図] 2SK79 の $I_D - V_{DS}$ 特性