




DATA SHEET FOR
TRANSFORMER # Q-4009172-E

Made for VIKTOR STOLBOVOY

Page 1 of 2

LEADS		SCHEMATIC				LEADS	
S#16/8"	0V	WHITE		BROWN	0V	S#12/8"	
S#16/8"	120V	YELLOW		BROWN	UO = 39.6V RMS 38V RMS / 12A RMS	S#12/8"	
S#16/8"	0V	ORANGE		ORANGE	0V	S#12/8"	
S#16/8"	120V	BLACK		ORANGE	UO = 39.6V RMS 38V RMS / 12A RMS	S#12/8"	
				BLUE	0V	S#20/8"	
				BLUE	UO = 12.3V RMS 60V RMS / 0.8A RMS	S#20/8"	
				GRAY	0V	S#20/8"	
				GRAY	UO = 12.3V RMS 60V RMS / 0.8A RMS	S#20/8"	
				VIOLET	0V	S#20/8"	
				VIOLET	UO = 18.8V RMS 18V RMS / 0.8A RMS	S#20/8"	
			GRN/YEL	STATIC SHIELD	S#18/8"		

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120/240V +/-10%
RATED PRIMARY CURRENT: 9.0/4.5A
RATED FREQUENCY: 50/60 Hz
TEMP. RISE AT RATED LOAD: 58 °C

DIMENSIONS/WEIGHT:

OD = 6.4"

H = 3.4"

WEIGHT = 17.9 LBS.

MOUNTING:

POTTED CENTER

FLAT BOTTOM

HOLE DIAMETER = 3/8"

CORE DATA:

CORE # 1200

CORE LOSS = 5.3 W

NO-LOAD CURRENT = 47 mA

Dimensions stated above are nominal. Tolerance is 10%.

MAGNETIC SHIELD = 60mm

DATA SHEET FOR

TOROID CORPORATION of MD



ISO 9001
Certified

TRANSFORMER # Q-4009172-E

Made for VIKTOR STOLBOVOY

page 2 of 2

OTHER SPECIFICATIONS: Transformer meets UL 506, EN 61558 and CSA C22.2 No. 66 standards.
Class B insulation.

Label:

SPEC DATE: 04/21/08

(Logo)

Transformer # Q-4009172-E
Made for VIKTOR STOLBOVOY
P/N

By: **MX**

(date code)

TOROID CORPORATION of MD

2020 Northwood Drive * Salisbury, MD 21801 * Tel: 410-860-0300 * Fax: 410-860-0302
e-mail: sales@toroid.com * web: www.toroid.com