

## Excel Export Setup File Parameters

Run Name: 8587- SO2100-8-XT4278-98.304

Path: \\Srv2\Production\Thermal Run Data\

Print: All Operator:

Row A: Measured FL

Ref F: F @ 25.00°C (Actual)

Run Start: 17-Mar-2015 6:22 pm

Run Finish: 17-Mar-2015 7:09 pm

S&A W2200 Rev: 5.75 Report: 2.20

Setup File:

\\Srv2\Production\QCC for all\FABO\XT4278

CL: 16.5pF

Crystal ID	FL ±5 ppm	RR Ohms	C0 pF	C1 fF	Q >90 k	F/T ±5 ppm	IT1 °C	ANGL '
A113	1.9	34.2	2.67	0.398	119	-1.6	28.6	1.17
A114	-0.3	32.7	2.64	0.408	121	-2.8	28.6	1.80
A115	2.4	32.4	2.68	0.413	121	-1.4	28.4	1.05
A118	0.5	33.6	2.65	0.400	120	-1.4	27.5	0.25
A119	1.8	32.9	2.61	0.415	119	-2.8	28.6	1.77
A120	-0.4	33.3	2.65	0.408	119	-2.8	28.6	1.73
A121	0.0	34.0	2.63	0.394	121	-2.0	28.6	1.41
A122	1.2	33.3	2.67	0.404	120	-3.7	28.9	2.20
B001	1.6	33.0	2.58	0.407	121	-2.0	28.3	1.35
B003	1.3	34.2	2.68	0.401	118	-3.1	28.7	1.92
B004	1.7	32.6	2.66	0.414	120	-3.0	28.7	1.87
B005	-0.6	33.4	2.63	0.411	118	-2.4	28.6	1.57
B008	2.2	33.7	2.65	0.400	120	-3.0	28.8	1.85
B010	-2.4	33.0	2.65	0.408	120	-3.6	28.7	2.16
B012	3.2	32.9	2.66	0.406	121	-2.5	28.5	1.61