

# Alpair 10 Driver Measured T/S Parameters

	<b>Spec</b>	Driver 1	Driver 2	<b>Average</b>	Difference	
fd	<b>40</b>	43.049	42.634	<b>42.842</b>	7.1%	Hz
Re	<b>5.4</b>	5.4	5.4	<b>5.4</b>	0.0%	ohm
Lvc	<b>0.070</b>	0.073	0.071	<b>0.072</b>	2.6%	mH
Qed	<b>0.390</b>	0.375	0.384	<b>0.380</b>	-2.7%	-
Qmd	<b>2.240</b>	2.526	2.513	<b>2.520</b>	12.5%	-
Qtd	<b>0.332</b>	0.326	0.333	<b>0.330</b>	-0.8%	-
BL	<b>5.83</b>	5.76	5.68	<b>5.72</b>	-1.9%	NA
Vad	<b>19.50</b>	18.23	18.53	<b>18.38</b>	-5.7%	liters
Sd	<b>90.0</b>	90.0	90.0	-	-	cm^2
SPL	<b>87.0</b>	87.7	87.6	<b>87.6</b>	0.7%	dB/W/m
Xmax	<b>8.5</b>	8.5	8.5	-	-	mm (1 way)
SPL	<b>88.7</b>	89.4	89.3	<b>89.3</b>	0.7%	dB/2.83V/m