

Product Categories

Specifications

Speaker

Electronic

Accessories

- Speaker Stand

Drivers

Nomial Impedance

VC Nominal Dia

Lowest Resonance Frequency

Effective Frequency Range

Output Sound Pressure Level

Input

Flux Density

Buzz & Rattle Test

Polarity

Baffle Opening

Magnet Dimenion / Weight

Weight

Dropping Test

Znom

Revc

Krm

Kxm

Erm

Exm

Sd

BL

Vas

Cms

Mms

Mmd

Fi

Fo

Qms

Qes

Qts

Pmx

Hvc

Hag

Xmx

Cmx

Cmo

θVc

8Ω ± 15% at 1.0V 1KHz

ψ42mm

FO=92Hz ± 5Hz at 1.0V

FO ~ 6KHz - 10dB 1M/1W

87dB/W/M ±3dB 500,600,700,800Hz

AVE

Rated Input 40W , Maximum Input

50W

12.43K ±10% GUASS

5.0V

POSITIVE - (LEFT) HAND TERMINAL

99mm

110 x 50 x22(mm) / 793g

1800g

1150mm 7.5° ± 2°

8 Ω

5.2 Ω

1.78 mΩ

3.778 mh

0.708

0.68

0.0075 sqm

7.2471 tm

2.4845 Litr

311.0361 um/n

10.1622 Gram

9.7887 Gram

87.919 Hz

89.520 Hz

3.529

0.566

0.488

40 Wrms

9 mm

4 mm

2.5 mm

2.5 mm