

ACROSS AUDIO			BRYSTON INPUT - BOM		
			Rev: 2.0		
品名	参数1	参数2	编号	备注	数量
1/4W电阻	100		R1, R2, R3		6
	20K		R4, R5, R6, R10, R16, R17		12
	3.48K	3.6K	R7		2
	15K		R8, R9		4
	100K		R11, R12		4
	150		R13, R14, R15		6
	68		R18, R19		4
	1.5K		R20		2
	1K		R21, R22		4
无极电容	471		C1, C2, C3		6
	22p		C6, C14, C15		6
	104		C7, C8, C9, C11, C12		10
电解电容	68uF/25V	47-100uF	C4, C5		4
	47uF/50V	10-100uF	C10, C13		4
二极管	E202		CRD1, CRD2	恒流二极管（2mA）	4
	1N914	1N4148	D1, D2, D3, D4, D5, D6		12
	1N4007	1N4004	D7, D8		4
	1/2W33V	30-33V	VD1, VD2	稳压二极管	4
三极管	PN100A		Q1, Q3, Q5	NPN	6
	PN200A		Q2, Q4, Q6	PNP	6
	2N5401	MPSA56	Q11	PNP	2
	2N5551	MPSA06	Q10	NPN	2
	MJE182		Q7, Q9	NPN	4
	MJE172		Q8, Q12	PNP	4
其他	90度弯脚2档 子开关		SW1		2
	台湾焊板RCA座 90度弯脚焊板		CON2		2
	纽崔克镀金卡农 母座90度弯脚焊		CON1		2
	散热		14*25*9mm		4