

最大 定格 (Ta=25°C)										電 気 的 特 性 (Ta=25°C)													
型 名	社 名	用 途	構造	V <sub>DS</sub> (V)		V <sub>GS</sub> (V)		I <sub>D</sub> (mA)		P <sub>D</sub> (mW)		T <sub>J</sub> (°C)		I <sub>SS</sub> (mA)		V <sub>DS(on)</sub> (V)		R <sub>DS(on)</sub> (mΩ)		g <sub>fs</sub> (mS)		f <sub>ts</sub> (MHz)	
				V <sub>DS</sub>	V <sub>GS</sub>	V <sub>GS</sub>	V <sub>DS</sub>	I <sub>D</sub>	P <sub>D</sub>	T <sub>J</sub>	I <sub>SS</sub>	V <sub>DS(on)</sub>	R <sub>DS(on)</sub>	g <sub>fs</sub>	f <sub>ts</sub>								
2N392	日 電	SW, チョーク	J	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2N393	"	"	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK411	東 芝	DC, 低雑音	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK412	"	"	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK413	"	DC, 低雑音	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK415	"	DC, 低雑音	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK416	日 立	入力	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK417	東 芝	オーディオ	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK418	"	DC	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK419	"	FIL, VHF	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK420	"	DC, VHF	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK421	"	DC, VHF	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK422	"	DC, VHF	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK423	"	DC, VHF	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK424	"	DC, VHF	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK425	"	DC, VHF	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK426	"	DC, VHF	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK427	"	DC, VHF	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK428	"	DC, VHF	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK429	"	DC, VHF	"	-40*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK430	東 芝	低雑音	"	-50*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK430ATM	"	低雑音	"	-50	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK433	三 菱	FIL, VHF	"	-30	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK434	"	低雑音	"	-20*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK437	日 電	FIL, RF/MIX	"	-50*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK438	三 菱	増幅用, DC MOS	"	-20*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK43A	"	"	"	20	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK439	ソニー	エレクトロニクス	J	-20*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK439A	"	エレクトロニクス	J	-20*	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK440	日 立	低雑音	"	-50	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							
2SK441	三 洋	FIL, RF/MIX	"	-18	40	-40	40	50	300	200	100*	20	-2	-5	20	10A							

[illegible]