

Type	current max (T=25°C)	Voltage available	Noise	housing	costs (Euro)	
AP2114	1A	3,3V	Low Output Noise: 30μVRMS 10Hz ≤ f ≤ 100kHz (No Load)	SOT-223 , TO-252-2(1), TO-252-2 (3), TO-252-2 (4), TO-263-3, SOIC-8 and PSOP-8.	0,314	AP2114H-3.3TRG1
LT1963	1,5A	3,3V	40μVRMS (10Hz to 100kHz)	■ 5-Lead TO-220, DD, 3-Lead SOT-223 , 8-Lead SO and 16-Lead TSSOP Packages	4,13	
ADP151	0,2A	3,3V	9μVRms 10 Hz to 100 kHz, VIN = 5 V, VOUT = 3.3 V)	5-lead TSOT package 6-lead LFCSP package 4-ball, 0.4 mm pitch WLCSP	0,93	
LT1763	0,5A	3,3V - 3,6V	20μVRMS over a 10Hz to 100kHz	8-lead SO and 12-lead, low profile (4mm × 3mm × 0.75mm) DFN packages.	3,7	
LT1086	1,5A	3,3V - 3,6V	0.003 % - TA = 25°C, 10Hz = ≤ f ≤ 10kHz 3,3V * 0,003% = 9mV	DDPAK-3	2,6	
				SOT89 -different Pin layout !!		

AMS1117-3.3

PIN CONNECTIONS

3 PIN FIXED/ADJUSTABLE
VERSION

- 1- Ground/Adjust
- 2- V_{OUT}
- 3- V_{IN}

SOT-223 Top View

