


## NPN EPITAXIAL SILICON TRANSISTOR

**CSC3503**  
**TO-126**  
**Plastic Package**



### PIN CONFIGURATION

1. EMITTER
2. COLLECTOR
3. BASE

Complement to CSA1381

### Applications

- Audio, Voltage Amplifier and Current Source
- CRT Display, Video Output
- General Purpose Amplifier

### ABSOLUTE MAXIMUM RATINGS ( $T_a = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER	SYMBOL	VALUE	UNITS
Collector - Base Voltage	$BV_{CBO}$	300	V
Collector - Emitter Voltage	$BV_{CEO}$	300	V
Emitter - Base Voltage	$BV_{EBO}$	5	V
Collector Current (DC)	$I_C$	100	mA
Collector Current (Pulse)	$I_{CP}$	200	mA
Total Device Dissipation, $T_C=25^\circ\text{C}$	$P_C$	7	W
$T_C=125^\circ\text{C}$		1.2	W
Junction and Storage Temperature	$T_J, T_{STG}$	-55 ~ 150	$^\circ\text{C}$

### THERMAL CHARACTERISTICS\* ( $T_a=25^\circ\text{C}$ unless otherwise specified)

PARAMETER	SYMBOL	MAX.	UNITS
Thermal Resistance, Junction to Case	$R_{\theta JC}$	17.8	$^\circ\text{C/W}$

\* Device mounted on minimum pad size


**ELECTRICAL CHARACTERISTICS\*** ( $T_a=25^\circ\text{C}$  unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Collector-Base Breakdown Voltage	$BV_{CBO}$	$I_C=10\mu\text{A}, I_E=0$	300			V
Collector-Emitter Breakdown Voltage	$BV_{CEO}$	$I_C=1\text{mA}, I_B=0$	300			V
Emitter-Base Breakdown Voltage	$BV_{EBO}$	$I_E=10\mu\text{A}, I_C=0$	5			V
Collector Cut-off Current	$I_{CBO}$	$V_{CB}=200\text{V}, I_E=0$			0.1	$\mu\text{A}$
Emitter Cut-off Current	$I_{EBO}$	$V_{EB}=4\text{V}, I_C=0$			0.1	$\mu\text{A}$
DC Current Gain	$h_{FE}^{**}$	$V_{CE}=10\text{V}, I_C=-10\text{mA}$	40		320	
Collector-Emitter Saturation Voltage	$V_{CE}(\text{sat})$	$I_C=20\text{mA}, I_B=2\text{mA}$			0.6	V
Base-Emitter Saturation Voltage	$V_{BE}(\text{sat})$	$I_C=20\text{mA}, I_B=2\text{mA}$			1	V
Current Gain Bandwidth Product	$f_T$	$V_{CE}=30\text{V}, I_C=10\text{mA}$		150		MHz
Output Capacitance	$C_{ob}$	$V_{CB}=30\text{V}, f=1\text{MHz}$		2.6		pF
Reverse Transfer Capacitance	$C_{re}$	$V_{CB}=30\text{V}, f=1\text{MHz}$		1.8		pF

**\*\* $h_{FE}$  CLASSIFICATION**

CLASSIFICATION	C	D	E	F
$h_{FE}$	40~80	60~120	100~200	160~320

### Package Outline and Dimension TO-126



DIM	MIN.	MAX.
A	7.4	7.8
B	10.5	10.8
C	2.4	2.7
D	0.64	0.88
E	2.25 TYP.	
F	0.39	0.63
G	4.5 TYP.	
L	15.7 TYP.	
M	1.27 TYP.	
N	3.75 TYP.	
P	2.9	3.2
S	2.5 TYP.	



Continental Device India Pvt.Limited  
An ISO/TS 16949, ISO 9001 and ISO 14001 Certified Company



## Customer Notes

### Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

## DISCLAIMER

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of  
Continental Device India Pvt. Limited  
C-120 Naraina Industrial Area, New Delhi 110 028, India.  
Telephone + 91-11-2579 6150, 4141 1112 Fax + 91-11-2579 5290, 4141 1119  
email@cdil.com www.cdil.com  
CIN No. U32109DL1964PTC004291