



Suited for pro audio as a mid/hi or full-range and monitor. Also recommended for bass guitar. Works well in sealed or vented enclosures.



Nominal Basket Diameter	12.0", 305 mm
Nominal Impedance*	8 Ω
Power Rating**	
Watts	250 W
Music Program	500 W
Resonance	44 Hz
Usable Frequency Range	58 Hz – 4.3 kHz
Sensitivity***	99.9 dB
Magnet Weight	7 oz.
Gap Height	.275", 7.0 mm
Voice Coil Diameter	2.5", 64 mm

Fs	44 Hz
Re	5.17 Ω
Le	0.43 mH
Qms	4.17
Qes	0.45
Qts	0.41
Vas	4.76 cu.ft., 134.88 liters
Vd	255.0 cc
Cms	0.36 mm/N
BL	10.69 T-M
Mms	37 grams
EBP	96
Xmax	4.90 mm
Sd	519.5 cm ²
Xlim	8.5 mm

Recommended Enclosure Volume	
Sealed	25.49–42.48 liters, 0.90–1.50 cu.ft.
Vented	32.56–127.43 liters, 1.15–4.50 cu.ft.
Driver Volume Displaced	0.050 cu.ft., 1.42 liters
Overall Diameter	12.38", 314.5 mm
Baffle Hole Diameter	11.06", 280.9 mm
Front Sealing Gasket	Yes
Rear Sealing Gasket	Yes
Mounting Holes Diameter	0.28", 7.1 mm
Mounting Holes B.C.D.	11.62", 295.2 mm
Depth	6.06", 153.9 mm
Net Weight	5.10 lbs , 2.31 kg
Shipping Weight	6.80 lbs , 3.08 kg

Aluminum voice coil
Polyimide former
Neodymium magnet
Vented core
Die-cast aluminum basket/ heatsink
Paper cone
Cloth cone edge
Solid composition paper dust cap



LEARN MORE AT EMINENCE.COM



From design and manufacturing to the stage or studio. Once you've experienced the performance of Eminence, you'll never accept anything else.

MISSION STATEMENT

Eminence is dedicated to providing the best Quality, Value and Service to meet our customers' needs.

FOOTNOTES

- * Please consult www.eminence.com for specifications of models with alternative impedances.
- ** Multiple units exceed published ratings evaluated under EIA 426A specification while tested in a free-air, non-temperature-controlled environment.
- *** The average output across the usable frequency range when applying 1W/1m into the nominal impedance. i.e: 2.83V/8Ω, 4V/16Ω. Eminence response curves are measured under the following conditions: All speakers are tested at 1W/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2 ft. x 2 ft. baffle is built into the wall with the speaker mounted flush against a steel ring for minimum diffraction | Carver PM-120 amplifier | 2700 cu. ft. chamber with fiberglass on all six surfaces (three with custom-made wedges).
- **** BETA 8CX, 10CX, and 12CX are coaxial speakers with tweeter sold separately. Published usable frequency response contingent upon use of ASD:1001 HF Driver.
- ***** Multiple units exceeded published ratings evaluated under EIA-426A or AES specification while mounted on Eminence's H290, H290S, or H2EA horn in a non-temperature-controlled environment.
- *****The average on axis output across the entire usable frequency range when applying 1W/1m into the nominal impedance, i.e. 2.83V/8Ω, 4V/16Ω. Eminence response curves are measured under the following conditions: All speakers are tested at 1W/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2ft x 2ft baffle is built into the wall with horn front mounted | Carver PM-120 amplifier | 2700 cu.ft. chamber with fiberglass on all six surfaces (three with custom-made wedges).

Prices, specifications and product cosmetics are subject to change without notice.

EMINENCE SPEAKER LLC

838 Mulberry Pike, Eminence, KY 40019



Follow us:

EMINENCE.COM

