

LDR TYPE NSL-32SR3

* = Sort Column

				LED	Current	Amps	*			
	1.00E-06	2.50E-06	5.00E-06	1.00E-05	5.00E-05	1.00E-04	5.00E-04	1.00E-03	2.50E-03	5.00E-03
LDR #	LDR Resistance Ohms									
2	4.30E+06	6.80E+05	1.60E+05	3.95E+04	3365	1373	306.5	181.5	100.1	67.6
9	5.40E+06	8.50E+05	2.00E+05	4.76E+04	3810	1490	310.8	179.3	95.9	63.4
7	4.12E+06	8.15E+05	2.08E+05	5.30E+04	4224	1654	330	186	96.7	62.8
4	3.24E+06	5.60E+05	1.39E+05	3.48E+04	3300	1404	332	199.8	111.6	75.3
13	6.90E+06	9.35E+05	1.97E+05	4.57E+04	3875	1563	343	201	109.1	73
14	4.00E+06	7.57E+05	2.00E+05	5.10E+04	4300	1721	355.3	201	104	67.2
6	3.90E+06	6.87E+05	1.74E+05	4.43E+04	4088	1692	388	230.3	126.7	84.8
3	8.00E+06	1.07E+06	2.21E+05	5.20E+04	4370	1763	389.7	229	124.9	83.5
5	4.93E+06	8.06E+05	1.90E+05	4.65E+04	4140	1713	391.7	232	127.4	85.6
21	7.31E+06	1.00E+06	2.17E+05	5.72E+04	4740	1870	396.2	229	122.6	81.2
17	6.77E+06	9.75E+05	2.16E+05	5.10E+04	4380	1770	398.3	236.1	130.3	88.3
18	3.46E+06	7.85E+05	2.12E+05	5.73E+04	4800	1950	405	229.6	119.7	77.7
16	2.43E+06	5.25E+05	1.48E+05	4.02E+04	3967	1690	411.8	249.3	139.2	94
12	4.92E+06	8.65E+05	2.15E+05	5.36E+04	4600	1877	412.6	240.5	129.5	85.7
1	1.38E+07	1.60E+06	3.12E+05	6.75E+04	5150	2016	419.1	240.9	128	84.2
19	2.78E+06	6.71E+05	1.92E+05	5.33E+04	4866	1990	424	244	130.4	86.7
11	6.42E+06	1.08E+06	2.68E+05	6.65E+04	5620	2195	452	258.2	135.7	89.1
8	1.80E+07	2.17E+06	3.97E+05	8.40E+04	6030	2315	489	281.5	149.8	97.6
10	2.43E+06	5.36E+05	1.63E+05	4.78E+04	5240	2250	509	292.1	151.3	96.3
15	4.10E+06	9.20E+05	2.63E+05	7.00E+04	6240	2480	519.4	295.1	153.1	98.7
20	2.03E+07	2.24E+06	4.34E+05	9.43E+04	7040	2676	541	308.4	163.1	107.3