

Technical Specification | Facette

Sensitivity (2.83 V/1 m): 84 dB

Recommended Amp. Power: Small size rooms: >50 watts
 Medium size rooms: >100 watts
 Large size rooms: -- watts

IEC Long Term Power Handling: >150 watts

Impedance, Nominal: 4 ohms
 Impedance, (20 - 200 Hz): 4.0 - 8.8 ohms
 Impedance, (200 - 20 kHz): 4.0 - 6.3 ohms
 Impedance, Phase Shift (20 - 200 Hz): -22.9° - +24.9°
 Impedance, Phase Shift (200 - 20 kHz): -1.7° - +13.2°
 Impedance, HF (200 kHz): 7.4 ohms

Frequency Response (+/- 4 dB): 40 Hz - 22 kHz

Resonance Frequency: 44 Hz

Internal Cabinet Volume: 18 litres

Bass Principle: Dynaudio-BLR (Back Loaded Radiator)

Weight: 14 kg

Dimensions (W x H x L): 280 x 1035 x 225 mm

Crossover: 2 way. Crossover is impedance corrected

Crossover Frequencies: 3200 Hz

Crossover Slope: Woofer: 6 dB/oct, Tweeter: 6 dB/oct

Connection: OCOS & Gold binding posts

Recommended Placing: Floor, free standing

Remarks: Tweeter: 28 mm soft dome.
 Magnetic fluid.
 Aluminium front.
 Pure aluminium wire voice coil.
 Rear chamber.
 double magnet system.

Woofer: 17 cm with 75 mm pure
 aluminium wire voice coil.

Passive Radiator: 17 cm

High quality polypropylene capacitors.
 Only high quality air coils are used.
 Special multi core air coils.

DYNAUDIO International GmbH

Ohepark 2
 21224 Rosengarten
 Germany
 Phone +49 (0)4108 - 4180 - 0
 Fax +49 (0)4108 - 4180 - 10
 E-Mail info@dynaudio.de