

W10N8-700

10" - 700 W - 96 dB - 8 Ohm



NOMINAL SPECIFICATIONS

Nominal Diameter	250 mm (10 in)
Overall Diameter	261 mm (10.28 in)
Bolt Circle Diameter	246 mm (9.69 in)
Baffle Cutout Diameter	230 mm (9.06 in)
Depth	141.3 mm (5.56 in)
Flange and Gasket Thickness	12.5 mm (0.49 in)
Net Weight	5 Kg (11 lb)
Shipping Box (Single Carton Box)	305 x 305 x 185 mm (12.0 x 12.0 x 7.3 in)
Shipping Weight	5.6 Kg (12.3 lb)

NOTES:

(1) 2 Hours Test According to AES 2-1984 Rev. 2003

(2) Maximum power is defined as 3dB greater than nominal power.

(3) $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$

(4) Maximum excursion before permanent damage

TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	7.3 Ohm
AES Power Handling (1)	700 W
Maximum Power Handling (2)	1400 W
Sensitivity (1W/1m)	96 dB
Frequency Range	60-4000 Hz
Voice Coil Diameter	100 mm (4 in)
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	22 mm (0.87 in)
Magnetic Gap Depth	12 mm (0.47 in)
Flux Density	1.3 T

THIELE & SMALL PARAMETERS

Fs	56 Hz
Re	5.5 Ohm
Qes	0.20
Qms	7.32
Qts	0.20
Vas	18 dm ³ (0.63 ft ³)
Sd	319 cm ² (49.4 in ²)
Xmax (3)	9.00 mm
Xdamage (4)	12.5 mm
Mms	64.8 g
Bl	24.7 N/A
Le	0.95 mH
Mmd	61.5 g
Cms	0.12 mm/N
Rms	3.11 Kg/s
Eta Zero	1.5 %

