



CAUTION 500 VOLTS AVAILABLE DISCONNECT POWER SUPPLY BEFORE SERVICING AND ALLOW 30 SECONDS FOR BLEEDERS TO DISSIPATE B+ VOLTAGE

TEST DATA

(MV) DENOTES TYPICAL 1K H₂ SIGNAL FOR 10 WATT OUTPUT (WITH PLUS INTO INPUT JACK) (USE 0.1 MFD 600 CAPACITOR IN SERIES WITH GENERATOR'S "HOT" LEAD)

CONTROL SETTINGS - EQUALIZERS AT MID POSITION
PRESENCE AT MINIMUM
OTHERS AT MAXIMUM

DEC. VOLTAGE READ WITH NO SIGNAL INPUT

FENDER MUSICAL INSTRUMENTS

CBS MUSICAL INSTRUMENTS
A DIVISION OF CBS INC.
FULLERTON, CALIFORNIA
U.S.A.

1. USED IN SOME VERSIONS
2. ALL RESISTORS 1/2W. 10%
ALL CAPACITORS AT LEAST 100 P.P.M.
NOTES: UNLESS OTHERWISE SPECIFIED

SAMPLES OF FIRST ARTICLE PARTS MUST BE APPROVED BY FENDER ROGERS RHODES R & D ENG. BEFORE STARTING PRODUCTION			
HEAT TREATMENT	UNLESS OTHERWISE SPECIFIED	DWN	DATE
FRACTIONS	TOLERANCES	CHK	DATE
ROCKWELL		APPRO	DATE
ANGLES		E.E.	DATE
FRACTIONS - WOOD			
HOLES - CURED			
BEND ANGLE			
HOLES - DRILLED & PIERCED			
SOFT ANGLES			
STRAIGHTENING			
UNMARKED ANGLES ARE 90°			
FINISH - TO DES. SPEC.			

Fender/Rogers/Rhodes
CBS MUSICAL INSTRUMENTS - A DIVISION OF CBS INC.
FULLERTON, CALIFORNIA 92631

PART NAME
SCHEMATIC - 200 WATT BASS AMPLIFIER W/LED

RELEASE ☒ **DATE** ☒ **SCALE** ☒ **MODE** ☒