

Surface Mount

# Monolithic Amplifier

DC-1 GHz

## Features

- InGaP HBT IF and RF amplifier
- Frequency range, DC to 1 GHz
- High gain, 25.1 dB typ. at 0.1 GHz
- +19.2 dBm typ. output power at 0.1 GHz
- High IP3, +38 dBm at 0.1 GHz
- Low noise figure, 2.7 dB typ.
- Unconditionally stable
- Low thermal resistance
- Transient protected
- Aqueous washable
- Protected by US patent, 6,943,629



## Applications

- Cellular
- Broadband
- Communication receivers & transmitters

## General Description

Gali74+ (RoHS compliant) is a wideband amplifier offering high dynamic range. Lead finish is SnAgNi. It has repeatable performance from lot to lot, and is enclosed in a SOT-89 package. It uses patented Transient Protected Darlington configuration and is fabricated using InGaP HBT technology. Expected MTBF is 500 years at 85°C case temperature. Gali74+ is designed to be rugged for ESD and supply switch-on transients.

## simplified schematic and pin description



| Function         | Pin Number | Description  |
|------------------|------------|--|
| RF IN            | 1          | RF input pin. This pin requires the use of an external DC blocking capacitor chosen for the frequency of operation.  |
| RF-OUT and DC-IN | 3          | RF output and bias pin. DC voltage is present on this pin; therefore a DC blocking capacitor is necessary for proper operation. An RF choke is needed to feed DC bias without loss of RF signal due to the bias connection, as shown in "Recommended Application Circuit". |
| GND              | 2,4        | Connections to ground. Use via holes as shown in "Suggested Layout for PCB Design" to reduce ground path inductance for best performance.  |



**Gali74+**

CASE STYLE: DF782  
PRICE: \$2.35 ea. QTY. (25)

**+ RoHS compliant in accordance  
with EU Directive (2002/95/EC)**

*The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.*

**Mini-Circuits®**  
ISO 9001 ISO 14001 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: [www.minicircuits.com](http://www.minicircuits.com)

RF/IF MICROWAVE COMPONENTS

ALL NEW  
**minicircuits.com**

REV. C  
M108520  
Gali-74+  
ED-10887/6  
MM/RS/CP/AM  
071026  
Page 1 of 4

## Electrical Specifications at 25°C and 80mA, unless noted

| Parameter   |                | Min. | Typ. | Max. | Units |
|---|----------------|------|------|------|-------|
| Frequency Range*                                  |                | DC   |      | 1    | GHz   |
| Gain  | f=0.1 GHz      | 20   | 25.1 |      | GHz   |
|   | f=1 GHz        |      | 21.8 |      |       |
|   | f=2 GHz        |      | 18.0 |      |       |
|   | f=3 GHz        |      | 15.3 |      |       |
|   | f=4 GHz        |      | 13.4 |      |       |
| Input Return Loss                                 | f= DC to 1 GHz |      | 21   |      | dB    |
| Output Return Loss                                | f= DC to 1 GHz |      | 12.5 |      | dB    |
| Output Power @ 1 dB compression                   | f=0.1 GHz      | 18   | 19.2 |      | dBm   |
|   | f=0.5 GHz      |      | 19   |      |       |
|   | f=1.0 GHz      |      | 18.3 |      |       |
| Output IP3  | f=0.1 GHz      |      | 38   |      | dBm   |
|   | f=0.5 GHz      |      | 37   |      |       |
|   | f=1.0 GHz      |      | 33   |      |       |
| Noise Figure                                      |                |      | 2.7  |      | dB    |
| Recommended Device Operating Current              |                |      | 80   |      | mA    |
| Device Operating Voltage                          |                | 4.3  | 4.8  | 5.3  | V     |
| Thermal Resistance, junction-to-case <sup>1</sup> |                |      | 120  |      | °C/W  |

\*Guaranteed specification DC-1 GHz. Low frequency cut off determined by external coupling capacitors.

## Absolute Maximum Ratings

| Parameter              | Ratings        |
|------------------------|----------------|
| Operating Temperature* | -45°C to 85°C  |
| Storage Temperature    | -65°C to 150°C |
| Operating Current      | 130mA          |
| Input Power            | 10dBm          |


Note: Permanent damage may occur if any of these limits are exceeded.

These ratings are not intended for continuous normal operation.

<sup>1</sup>Case is defined as ground leads.

\*Based on typical case temperature rise 6°C above ambient.

## Product Marking



## Additional Detailed Technical Information

Additional information is available on our web site. To access this information enter the model number on our web site home page.

## Performance data, graphs, s-parameter data set (.zip file)

## Case Style: DF782

Plastic package, exposed paddle, lead finish: tin/silver/nickel


## Tape &amp; Reel: F55

## Suggested Layout for PCB Design: PL-019

## Evaluation Board: TB-409-74+

## Environmental Ratings: ENV08T2

## Recommended Application Circuit



Test Board includes case, connectors, and components (in bold) soldered to PCB

| R BIAS |  |
|--------|--|
| Vcc    | "1%" Res. Values (ohms)<br>for Optimum Biasing |
| 7      | 28.7   |
| 8      | 41.2   |
| 9      | 53.6   |
| 10     | 66.5   |
| 11     | 78.7   |
| 12     | 90.9   |
| 13     | 102  |
| 14     | 115  |
| 15     | 127  |

## ESD Rating

Human Body Model (HBM): Class 1C (1000v to < 2000v) in accordance with ANSI/ESD STM 5.1 - 2001

Machine Model (MM): Class M2 (100v to < 200v) in accordance with ANSI/ESD STM 5.2 - 1999

## MSL Rating

Moisture Sensitivity: MSL1 in accordance with IPC/JEDECJ-STD-020C

| No. | Test Required                | Condition   | Standard                    | Quantity |
|-----|------------------------------|---|-----------------------------|----------|
| 1   | Visual Inspection            | Low Power Microscope Magnification 40x  | MIP-IN-0003 (MCT spec)      | 45 units |
| 2   | Electrical Test              | Room Temperature  | SCD (MCL spec)              | 45 units |
| 3   | SAM Analysis                 | Less than 10% growth in term of delamination  | J-Std-020C (Jedec Standard) | 45 units |
| 4   | Moisture Sensitivity Level 1 | Bake at 125°C for 24 hours<br>Soak at 85°C/85%RH for 168 hours<br>Reflow 3 cycles at 260°C peak | J-Std-020C (Jedec Standard) | 45 units |

## MSL Test Flow Chart

