



EXPRESS

 **6 items**

(/)

Menu

Search for products

SALE GRS PT6816-8 8" Planar Slim Tweeter 8 Ohm

★★★★★ [Read 3 Reviews](#) | [17 Questions, 50 Answers](#) or [Write a Review](#)

GRS (/brand/GRS)
Part # **272-128**



SALE PRICE \$39.98

Reg. Price: ~~\$49.98~~

Save \$10.00 (20%)

Ships next business day.
[Details](#)

In Stock

Quantity:

[Add to Cart](#)

[Request Large Qty Quote \(requestcustomquote/33703\)](#)

FREE SHIPPING available on orders over \$99.00 in the US.
[Details](#)

60 Day No Hassle Return Policy
[\(/Return-A-Product\)](#)

[Request Large Qty Quote \(requestcustomquote/33703\)](#)

[+ Add to Project List](#)

Capable of delivering wide bandwidth with low distortion, the GRS PT6816-8 open back planar driver has the ability to perform well from upper midrange to the highest frequencies. With an extremely lightweight diaphragm and a neodymium motor system, this driver is capable of excellent transient response with amazing dynamics. The open back construction produces true dipole radiation which is ideal for use in open baffle designs. With a narrow footprint and minimal flange, the PT6816-8 is also ideal for line array use.

Key Features

Accessibility low mass diaphragm provides excellent transient response and accuracy

- narrow design to deliver excellent off axis consistency

- Narrow design to deliver excellent on-axis consistency
- Multiple neodymium magnets in push pull arrangement for incredible control and low distortion
- Open back delivers true dipole radiation making this driver ideal for open baffle line array designs
- Linear impedance simplifies crossover design
- Shallow mounting depth for use in low profile designs

Share



Overview

Specifications

Q&A

Reviews

Manuals & Resources

◀ Back

GRS PT6816-8 8" Planar Slim Tweeter 8 Ohm

The GRS PT6816-8 open back planar midrange/tweeter is designed to deliver low distortion with dynamic response. Thanks to a lightweight damped polyimide diaphragm that is driven by 18 powerful neodymium magnets in a push-pull arrangement, this driver is capable of incredible transient response and wide bandwidth. The almost linear 6.4 ohm impedance makes crossover design simple and minimizes the number of components required to achieve your required roll off. In addition, the open back design gives this tweeter true dipole radiation making it the perfect choice for use in open baffle speaker designs. With wide dispersion capabilities and minimal mounting flange, the PT6816-8 is an excellent choice for use in high output line arrays.

Product Details

Brand	GRS
Model	PT6816-8
Part Number	272-128
UPC	848864061245
Unit of Measure	Each
Weight	0.8

Product Specifications

Cutout Diameter	6.89" x 1.65
-----------------	--------------

Accessibility

Product Specifications

Tweeter Type	Planar
Power Handling (RMS)	30 Watts
Impedance	8Ω
Frequency Response	320 to 20,000Hz
Sensitivity	94dB 2.83V/1m

Thiele-Small Parameters

DC Resistance (Re)	6.4Ω
Voice Coil Inductance (Le)	0.02mH
Mechanical Q (Qms)	6.19
Total Q (Qts)	4.57

Mounting Information

Overall Outside Diameter	7.875" x 2.56"
Depth	0.47"

[Overview](#)[Specifications](#)[Q&A](#)[Reviews](#)[Manuals & Resources](#)

(/GRS-PT6816-8-8-Planar-Slim-Tweeter-8-Ohm-272-128)

SAVE

GRS
PT6816-8
8" Planar
Slim

Ends
in
1-55-39

Accessibility

