



SPECIFICATIONS

Transistors & Diodes used:	2SB-257 x 2, 2SB-54 x 6, 2SB-56 x 2, 2SB-43 x 2, 2SD-43 x 2, 2SB-202 x 4, 2SB-26 x 4, 1S-100 x 2. (22 transistors, 2 diodes)
Output:	Max. 12 W x 2 Undistorted: 10 W x 2 (Harmonic Distortion less than 2%)
Input:	MAG 10W/16 ohms with 3 mV input; TUNER, TAPE, AUX 1, AUX 2 10W/16 ohms with 15 mV input
Output Impedance:	3 ohms
Load Impedance:	4 — 16 ohms
Low Output Distortion:	less than 0.5% at 10 mW/16 ohms
Tone Control:	50c/s { +9dB -11dB } 10kc { +6dB -13dB }
Loudness Control:	100 c/s +8 dB; 10 Kc +4 dB
Rumble Filter:	50 c/s -9dB
Scratch Filter:	10 Kc -12 dB
Equalization:	RIAA (LP record)
Residual Noise:	3 mV/16 ohms.
Warm-up Time:	0.5 sec.
Critical Inner Temperature:	55°C
Power Source:	AC 100V, 117V 50—60 c/s 30VA DC 12—18V 15VA at 18V
Weight:	(W) 301 m/m x (H) 186 m/m x (D) 81 m/m
Dimensions:	4.4 Kg

