



US007402922B2

(12) **United States Patent**
Springer et al.

(10) **Patent No.:** **US 7,402,922 B2**
(45) **Date of Patent:** **Jul. 22, 2008**

(54) **ACOUSTIC WAVE GENERATING
APPARATUS AND METHOD**

(75) Inventors: **Jeffery T. Springer**, La Honda, CA
(US); **James L. Kirschman**, El Dorado
Hills, CA (US); **Robert M. O'Neill**,
Oxford, MS (US); **Conrad P. Sandoval**,
Roseville, CA (US); **Joseph B. Young**,
Paducah, KY (US)

(73) Assignee: **Renaissance Sound LLC**, El Dorado
Hills, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 353 days.

(21) Appl. No.: **11/294,097**

(22) Filed: **Dec. 5, 2005**

(65) **Prior Publication Data**

US 2008/0073981 A1 Mar. 27, 2008

Related U.S. Application Data

(60) Provisional application No. 60/633,924, filed on Dec.
6, 2004, provisional application No. 60/709,425, filed
on Aug. 19, 2005.

(51) **Int. Cl.**

H02K 41/00 (2006.01)

H04R 25/00 (2006.01)

H04R 9/06 (2006.01)

(52) **U.S. Cl.** **310/15; 310/36; 381/396;**
335/209; 335/238

(58) **Field of Classification Search** 310/12,
310/15, 36; 335/209, 222, 229, 238, 285;
381/396

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,751,573 A 6/1956 Millington
3,416,804 A 12/1968 Christie
3,452,836 A 7/1969 Carsello

3,582,875 A	6/1971	Van Wambeek	
3,648,999 A	3/1972	Bauer	
3,984,707 A *	10/1976	McClintock	310/15
4,064,376 A	12/1977	Yamada	
4,259,653 A *	3/1981	McGonigal	335/230
4,385,210 A	5/1983	Marquiss	
4,680,492 A	7/1987	Tamura	
4,710,656 A	12/1987	Studer	
4,792,978 A	12/1988	Marquiss	
4,827,163 A *	5/1989	Bhate et al.	310/15
4,924,123 A *	5/1990	Hamajima et al.	310/15
4,937,481 A *	6/1990	Vitale	310/15
5,187,398 A	2/1993	Stuart	
5,231,336 A	7/1993	Van Namen	
5,341,054 A	8/1994	Tal	
5,424,592 A	6/1995	Bluen	
5,894,263 A	4/1999	Shimakawa	
5,896,076 A *	4/1999	van Namen	335/229
5,999,633 A	12/1999	Imai	
6,256,397 B1 *	7/2001	Komatsu	381/396
6,600,399 B1	7/2003	Tandafir	
7,078,832 B2 *	7/2006	Inagaki et al.	310/12
2003/0142845 A1 *	7/2003	Miyamoto et al.	381/396

* cited by examiner

Primary Examiner—Tran Nguyen

(74) *Attorney, Agent, or Firm*—Jones, Tullar & Cooper, PC

(57) **ABSTRACT**

A tactile wave generating apparatus and method to generate amplified low frequency waves which are then transmitted as tactile waves into a structure and/or to a persons anatomy. There is a housing in which is positioned a drive section that in turn comprises a magnet section that moves upwardly and downwardly as an inertial mass, two coils on opposite sides of the magnet and two flux path return plates for the coils. Each coil comprises upper and lower longitudinally aligned generally linear coil portions which drive the magnet section upwardly and downwardly. The magnet section is supported by upper and lower interconnecting sections that resiliently resist the up and down motion of the magnet section and restrain the magnet section to move up and down within close tolerances.

13 Claims, 15 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9






FIG. 11




FIG. 12




FIG. 13




Fig. 14




FIG. 15




FIG. 16





FIG. 17



1

ACOUSTIC WAVE GENERATING APPARATUS AND METHOD

RELATED APPLICATIONS

This application claims priority benefit of U.S. Ser. No. 60/709,425 filed on Aug. 19, 2005, and U.S. Ser. No. 60/633,924, filed on Dec. 6, 2004, with the entire disclosure of both of these being incorporated herein by reference.

BACKGROUND OF THE INVENTION

a) Field of the Invention

The present invention relates to a tactile wave generating apparatus and method, and more particularly to generating amplified low frequency waves which are transmitted as tactile sound into a structure and/or to a person's anatomy. Further the present invention relates to a system where the low frequency tactile waves may be transmitted to the person's body while the full audible waves are being transmitted to the person.

b) Background Art

Electroacoustic transducers such as loudspeakers for use in music or movie soundtrack reproduction are well known. In traditional prior art sound reproduction systems, large, powerful speakers move large amounts of air to permit a listener to feel the low frequency of sound. Listeners enjoy live concerts, in part, because they want to feel the sound pressure upon their bodies.

In recent years, one of the more important trends in the audio industry is that of "tactile sound" which may be described as "vibro-acoustic" or "vibro-tactile" stimulation. With tactile sound the realism of the listening experience can be enhanced by transmitting tactile waves into the person's body. For example, this could be done by vibrating the listener's seating surface of a chair or other furniture or structures. These tactile waves are able to be sensed within the person's body to add another dimension to the person's listening experience.

The initial application of these devices were as sub woofer replacements or sub woofer augmentation devices. The addition of higher frequency material began to demonstrate the potential of wider bandwidth devices and the associated additional dimensions that vibro-tactile stimulation brings to the overall experience. There are many parameters that need to be evaluated when designing and/or selecting a vibro-technical device for inclusion in music and/or an entertainment system. For example, bandwidths, efficiency and power handling need to be understood. These parameters can play a big role not only in the device selection but in the amplifier selection as well.

It is well understood in the loud speaker industry that sufficient bandwidths (i.e., flat frequency response with sufficient low frequency and high frequency limits) is critical for high fidelity reproduction. Vibro-tactile devices, like loud speakers, are devices that must be properly designed to refine the required bandwidth for accurate response.

It is with these and other considerations being kept in mind that the design of the embodiments of the present invention were created.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side elevational view showing the apparatus of an embodiment of the invention being mounted in its operating position attached to a platform of a seat of a chair;

2

FIG. 2 is a transverse sectional view of a first embodiment, taken generally along line 2-2 of FIG. 3;

FIG. 3 is a sectional view of the embodiment of FIG. 3 taken generally along a longitudinal axis, and showing cross sections at different locations located in the four quadrants of FIG. 3;

FIG. 4 is a side elevational view showing only one coil of the coil section of this embodiment of FIGS. 2 and 3;

FIG. 5 is a plan view of one of the interconnecting frame subsections of the first embodiment;

FIG. 6 shows the interconnecting frame section of FIG. 5 in an isometric view;

FIG. 7 is a partially exploded isometric view of the first embodiment of FIGS. 2-6;

FIG. 8 is a isometric view of the housing of the apparatus of FIG. 7, with one of the end covers being removed for purposes of illustration;

FIG. 9 is a cross sectional view of the apparatus of a second embodiment, with a cross section being taken perpendicular to the longitudinal axis;

FIG. 10 is a sectional view taken along line 10-10 of FIG. 9;

FIG. 11 is a view taken from the same viewing location as in FIG. 10, showing one coil of the coil section;

FIG. 12 is a plan view taken along line 12-12 of FIG. 9, illustrating an interconnecting section of the first embodiment;

FIG. 13 is an isometric view of FIG. 12;

FIG. 14 is a second design of an interconnecting section of the second embodiment;

FIG. 15 is an isometric view showing the mounting structure of the second embodiment;

FIG. 16 is an plan view of yet another design of a positioning section which could be used in either of the first or second embodiments; and

FIG. 17 is a sectional view which is substantially the same as FIG. 2, but with the numerical designations removed and certain dimensional relationships being illustrated.

EMBODIMENTS OF THE PRESENT INVENTION

1) A First Embodiment

a) General Description of the First Embodiment

A first embodiment of the present invention is illustrated in FIGS. 1-8 and is arranged to transmit low frequency acoustic waves into a structure, such as a chair, so that these waves are transmitted into a person's body.

It is believed that a better understanding of this first embodiment will be obtained by first describing the main components of the wave generating apparatus 10 of the first embodiment, and then providing a rather brief description of how this apparatus 10 functions in its operating position where it is mounted to a structure such as a chair 12, as shown in FIG. 1. Then this will be followed by a more detailed description of this first embodiment.

The first embodiment of the acoustic wave generating apparatus 10 of the present invention will now be described more generally with reference to FIGS. 2 through 8. Reference will first be made to FIG. 2, which is a cross sectional view of this apparatus 10 of the first embodiment taken approximately at line 2-2 of FIG. 3.

In this first embodiment of the apparatus 10, in terms of function most all of the components of this embodiment will be part of either a mounting section 14 or an inertial section

3

16. These two sections 14 and 16 are operatively connected to one another by an interconnecting positioning and force transmitting section 18 in a manner that the inertial section 16 reciprocates relative to the mounting section 14.

The mounting section comprises a housing 20, which is shown attached to the chair 12 to transmit to the seat of the chair 12 the inertial forces generated by the relative reciprocating motion between the inertial section 16 and the mounting section 14. (For convenience, in the following text the interconnecting positioning and force transmitting section 18 will simply be referred to as the interconnecting section 18).

The relative reciprocating movements of the sections 14 and 16 is accomplished by means of a drive section 22 which comprises two main components, namely a coil section 24 that is fixedly mounted in the housing 20 as part of the mounting section, and a magnet section 26 which is a major part of the inertial section 16. To facilitate the description of this first embodiment, the apparatus 10 will be considered as having a longitudinal axis 28 (FIG. 3), a transverse axis 30 (FIG. 2) perpendicular to the longitudinal axis 28, and a vertical axis 32 which is perpendicular to both the longitudinal axis 28 and the transverse axis 30.

The terms "upper" and "lower" shall be used in this text for convenience of description, with the understanding that in actual practice, the apparatus 10 could be positioned in different orientations where the apparatus 10 could be at an inverted orientation, or in a lateral orientation, etc.

As indicated earlier in this text, this embodiment of the apparatus 10 is designed to generate acoustic waves and transmit these directly into a structure, such as a seat platform 33 of the chair 12. In FIG. 10, the apparatus 10 is shown as having the housing 20 of the mounting section 12 directly connected to the bottom panel of a seat platform 33 of a chair 12. In this first embodiment the low frequency acoustic wave is generated by transmitting an amplified low frequency audio signal (e.g. 40 to 45 Hz) into the coil section 24 of the drive section 22, causing a relative oscillating movement (i.e. back and forth movement) of the inertial section 16 relative to the mounting structure 14 which in turn causes the acoustic wave to be transmitted directly into the chair seat as shown in FIG. 1. At the same time, there can be a speaker (shown schematically at 34) or earphones transmitting audible musical sound waves to the listener, and the low frequency acoustic waves can coincide with those of the audible musical sound waves. The effects of this will be discussed later in this text.

Also, present analysis indicates that the apparatus 10 is able to generate and transmit (in addition to a lower frequency base waves) tactile and/or acoustic waves up to 300 or possibly up to even 600 Hz or higher. More specifically the frequencies could range from a base frequency (e.g. 40 to 45 Hz) upwardly in 5 Hz increments (i.e., 50 Hz, 55 Hz, etc.) up to the 600 Hz level (or possibly higher). Also, the fundamental or base frequency could vary from 40 to 45 Hz downward in 5 Hz increments to even about 20 Hz.

b) A More Detailed Description of the First Embodiment

To begin now, the more detailed description of the apparatus 10 of this first embodiment, reference is again made to FIG. 2, and also to FIG. 7. It can be seen that in cross section the housing 20 has a main housing section 35 which has what can be described as an exaggerated hour glass configuration or an I beam configuration, and is made up of three sections, namely, upper and lower housing sections 36 and 38 of a greater width dimension, and a middle section 40 having a lesser width dimension. The upper and lower housing sec-

4

tions 36 and 38 are identical (or substantially identical) to one another, so the following description of the upper housing section 36 is meant to apply as well to the lower housing section 38.

The upper section 36 of the housing structure 20 has a top plate 42 which has an overall rectangular platform configuration and two rectangular side plates 44 extending downwardly from lateral outside edges of the upper plate 42. The lower edges of the side plates 44 each connect to inwardly extending transition plates 46 that have an inward and moderately downward slope. The lower housing section 38 of the housing 20 likewise has a bottom plate 42, the side plates 44, and the inwardly and moderately upwardly sloping transition plates 46, so that the lower section 38 is a mirror image of the upper section 36.

The middle housing section 40 comprises two rectangular intermediate vertically and longitudinally aligned parallel middle side plates 48 having upper and lower edge portions which join to, respectively, the inner edge portions of the upper transition plates 48 and to the inner edges of the lower transition plates 46.

The housing structure 20 also comprises two end plates 50 which may be substantially identical to one another and which are positioned at opposite ends of the main housing section 35. These can best be seen in FIG. 7. For purposes of illustration, one of the two end plates 50 is shown as being separated from the housing structure 12. The second end plate 50 is connected to the opposite end of the housing structure 10 and only two edge portions 52 and 54 can be seen. The two end plates 50 each have four corner located openings 56 to match with corner openings 57 of the housing section 35, so that the end plates 50 can be joined to the end portions of the main housing section 35 by connecting screws, bolts or other connectors.

The housing 20 of the mounting section 14 can be made of metal, plastic or some other material as a rigid unitary structure, such as being made by being machined, molded, extruded, casted and/or made of components welded, bonded, or otherwise joined to one another.

The aforementioned coil section 24 comprises two coils 58 which are positioned on opposite sides of the magnet section 26. As can be seen in FIG. 4, each coil 58 is fixedly connected to the interior surface 60 of one of two rectangular magnetically permeable return path steel plates 62 that are in turn connected to the interior surfaces of the side plates 48 of the middle housing section 34 of the housing 20. These plates 62 are also considered to be part of the coil section 24 and are thus also part of the mounting section 14. The two coils 58 are (or may be) identical, and each has a "racetrack" configuration, where there are upper and lower longitudinally aligned linear parallel middle coil sections 64 and 66 respectively, with the adjacent end portions of these two coil sections 64 and 66 being connected by oppositely positioned end coil portions 68 which in this embodiment are with 180° curves with the coil sections 64 and 66 having a straight line configuration. Each of these coils 58 has multiple windings, and each winding can be made in the form of a flat ribbon of an electrically conductive material which is coated by a suitable insulating material and which is wound in layers to form the "racetrack".

The aforementioned magnet section 26 comprises a rectangularly shaped magnet 70, upper and lower pole plates 72 and 74, respectively, fixedly connected to the upper and lower surfaces of the magnet 70, and upper and lower tuning members in the form of rectangular tuning blocks 76 and 78 positioned against and fixedly connected to the upper and

5

lower surface of the pole plates **74** and **76**, respectively. These tuning blocks **76** and **78** may be made of brass.

The configuration of the magnet **70** is a rectangular prism having parallel side surfaces **80**, parallel end surfaces **82**, and parallel upper and lower surfaces **84**, with each of these surfaces **80**, **82**, and **84** having a rectangular configuration, with adjoining surfaces meeting at a right angle. The tuning blocks **76** and **78** each have the configuration of a right angle rectangular prism, having parallel side surfaces, parallel bottom and top surfaces, and parallel end surfaces **86** (the side surfaces and upper and lower surfaces not having numerical designations simply for the purpose of illustration so that the drawings do not become too cluttered with numerals). The end surfaces **86** of the tuning blocks **76** and **78** extend a moderate distance beyond the end surfaces **82** of the magnet **70**.

The two pole pieces, **72** and **74**, each have the overall configuration of a rectangular prism, except that each corner portion of the pole pieces at its end locations has a cutout to form the two end portions **88** of each pole piece **72** and **74** of a reduced width dimension that is less than the width dimension of the main middle portion **71** of the magnet **70** (see FIG. 2 where the transverse surfaces at the base of the end portion **88** are designated **90**, and also FIG. 7).

However, the middle section **91** of the pole pieces **72** and **74** which extend between the end portions **82** of the magnet **70** have a width dimension moderately greater than that of the magnet **70** so that the side surfaces **92** of middle portions **91** of the pole pieces **72** and **74** extend laterally a short distance beyond the side surfaces **80** of the magnet **70**. Thus, these side surface portions **92** of the middle portions of the upper and lower pole pieces **72** and **74** define upper and lower longitudinally extending flux gaps **94** (see FIG. 2) which are positioned so that when the magnet section **26** is in its middle neutral position, the side surface portions **92** of the middle portions pole pieces **72** and **74** are centered relative to the upper and lower middle coil sections **64** and **66**. These flux gaps **94** are in large part occupied by the longitudinally aligned coil portions **64** and **66**.

The side surfaces **96** of the two tuning blocks **76** and **78** are vertically aligned with the side surfaces of **80** of the magnet **70**, and the end surfaces **86** of the tuning blocks **76** and **78** are transversely and vertically parallel to the end surfaces of the pole pieces **72** and **74**.

The magnet **70**, the pole pieces **72** and **74**, and the tuning blocks **76** and **78** are stacked one on top of the other as shown in FIG. 2 so that these are all in vertical alignment with each other, and centered along the longitudinal axis.

As can be seen in viewing FIGS. 3 and 7, the transversely and laterally aligned end surface portions **82** of the magnet **70** and the transversely aligned corner surface portions **90** of the pole pieces **72** and **74** lie in the same transverse vertical plane and terminate a short distance longitudinally inwardly from the location (indicated by the line **102**) in FIG. 3 where the end curved coil end portions **68** of the two coils **58** join integrally to the upper and lower straight coil sections **64** and **66**. Also, as can be seen in FIG. 2, the lateral outer side surfaces **92** of the main middle portions **91** of the two pole pieces **72** and **74** are positioned a short distance beyond the side surfaces **80** of the magnet **70** to form the upper and lower relatively narrow gaps **94** in which the upper and lower longitudinally aligned coil sections **64** and **66** are located.

As can be seen in FIG. 2, the magnet section **22** is in a neutral center position so that the two pole plates **72** and **74** are positioned at the mid height of, respectively, the upper and lower intermediate straight coil sections **64** and **66**.

6

The aforementioned interconnecting positioning and force transmitting section (now referred to as the "interconnecting section **18**") comprises upper and lower interconnecting sub-sections in the form of interconnecting frames **104**, (see FIGS. 5 and 6). These upper and lower frames **104** are (or may be) identical (or substantially identical to one another), except for being mirror images of one another. Accordingly, the following description of the upper frame **104** is intended to apply to the lower frame **104**.

Each of the interconnecting frames **104** can be considered as having a longitudinally aligned lengthwise center axis **106** which is spaced vertically from, and vertically aligned with, the main longitudinal axis **28** and a transverse axis **107**. Each frame **104** comprises a pair of longitudinally aligned housing connecting portions in the form of connecting edge members **108**, a center longitudinally aligned magnet connecting portion in the form of a connecting member **110**, and two intermediate connecting portions **111**, which are on opposite sides of the lengthwise center axis in the form of a plurality of cross members **112**. These members **108**, **110**, and **112** can be made as a single integral molded plastic piece.

Each of the housing connecting edge members **108** comprises a longitudinally extending connecting flange or rib **114** which has a vertically aligned width dimension moderately greater than the thickness of its adjacent cross member **112**, so as to have upper and lower portions forming upper and lower elongate raised portions relative to the cross member **112**. Each side plate **44** of the housing **20** has formed at an inner surface a longitudinally aligned slot **116** (see FIG. 2), which has a "T" shaped cross section so as to have an expanded interior portion and a narrower longitudinal gap. Thus, when the flange or rib **114** is aligned with its related slot **116** and slid into engagement, the flange or rib **114** is retained in its slot **116**.

The magnet connecting member **110** has two connecting end portions **118**, with each end portion **118** having a flattened moderately recessed upper surface portion **120** with a through opening **122** extending downwardly from the flat recessed surface portion **120** (see FIG. 2) to receive a screw or bolt **124**. The head **126** of the screw or bolt **124** (see FIG. 2) presses against the surface portion **120**, with the shank **128** extending through the opening **122** and through openings made in the end portions of the pole pieces **72** and **74** and of the tuning blocks **76** and **78** (see FIGS. 2 and 7). There is a fastener **130** at the lower end of the screw or bolt **124**. Thus, the two bolts **124** at opposite end portions **86** of the pole pieces **72** and **74** and of the tuning blocks **76** and **78** make a rigid connection of these components with the two magnet connecting members **110** of the interconnecting frames **104**, with the magnet **70** sandwiched in the middle, so that these components (i.e. the magnet **20**, the pole pieces **72** and **74**, the tuning blocks **76** and **78**, and the magnet **70** along with the central portions of the frames **104**) function as one unit which comprises the inertial section **16**.

The cross members **112** are arranged in four transversely aligned pairs which extend transversely between the two housing connecting edge members **108** and the magnet connecting member **110**. At the center location of each of these cross members **112**, the cross members **112** are fixedly joined to the centrally located magnetic connecting member **110**. (As indicated earlier herein, this entire interconnecting sub-section **104** can be made as one integral plastic piece molded as a single piece.) Thus, these cross members are anchored at the middle location to function as cantilever beam suspension members for the magnet section **26**.

The vertical thickness dimension of the magnet connecting member **110** is substantially greater than that of the cross

members 112. The horizontal width dimensions of the cross members 112 are substantially greater than their vertical thickness dimensions so that the cross members 112 are sufficiently resilient to enable the magnet section to move back and forth in a vertical direction and yet provide a sufficient restoring force to bring the magnet section 26 back toward its neutral position, but are highly resistant to any transverse or longitudinal movement.

A pair of wire terminals 132 are mounted at the outside surface portions of the front end of each of the middle side plates 48. Each terminal 132 has an outside connecting location 134 (see FIG. 7) and is retained in its mounted position by means of a connecting screw 136 (see FIG. 7). The wires extending from the terminals 132 to the coils 58 are designated 138. Longitudinally aligned connecting channels 140 (see FIG. 2) are provided in the housing 20 at juncture locations of the side plates 48 and the transition plates 46.

c) Assembly and Operation of the First Embodiment

To assemble the apparatus 10, the magnet section 26 can be assembled by placing the magnet 70, the pole pieces 72 and 74, the tuning blocks 78 and the interconnecting frames 74 in the proper stacked relationship and then connecting these together by means of the screws or bolts 124. Then this assembly can be placed in alignment with the housing 20, and then moved into the chamber 140 defined by the housing 20. The internal wire connections are made between the wire terminals 132 and the coils 58. Then the end plates 50 can be connected to the end portions of the main housing structure 20 and connected by the connecting screws 142 at the sealing openings 56. A sealing gasket 143 can be provided for each of the end plates 50.

The lower plate 42 of the lower housing section 38 has along its outer edges a pair of oppositely positioned laterally extending mounting flanges 144 (see FIG. 4), with each flange 144 being provided with a plurality of connecting openings 146 at evenly spaced locations along its length. To mount the apparatus 10 to a structure, such as the panel 34 of the chair 12, lower plate 42 of the housing 20 is placed against the panel 34 of the chair 12 and then bolts or fastening screws are inserted through the openings 146 to connect the apparatus 10 firmly to the chair panel 34.

With the apparatus 10 assembled, the electrical connections made, and the apparatus 10 connected to the panel 34 of the chair seat, the low frequency amplified signal is transmitted through the terminals 132 to cause the two electric currents to pass through the coils 58. The interaction of the magnetic fields created by the current flow through the coils 58 with the magnetic field of the magnet section 26 to cause the up and down movement of the magnet section 26 along with the entire inertial section 16.

As described previously in this text, the magnet section 26 is normally in the neutral position where the upper and lower middle or intermediate linear coil sections 64 and 66 are centered in the gaps 94 defined by the central portions 91 of the pole pieces 72 with the adjacent portions of the return path side plates 62, with the upper and lower intermediate coils sections 64 and 66 being located in those gaps 94.

Thus, the oscillating electromagnetic force causes the magnet section 26 to move upwardly and downwardly in the chamber 140 defined by the housing 20. The magnet section 26, functioning as part of the inertial mass 16, then oscillates upwardly and downwardly relative to the mounting structure 14 which comprises mainly the housing 20 along with the return path plates 62 and the other components that are fixedly attached to the housing 20.

As the inertial structure 16 moves in an oscillating manner upwardly and downwardly, there is an equal and opposite reaction transmitted from the housing 20 into the chair panel 36. To describe this more specifically, as the magnetic fields in the coils 58 create a force to move the magnet section 26 as part of the inertial structure 16 in one direction, the inertial force generated by the accelerating inertial structure 16 is reacted back through the magnetic field through the coils 58 which are fixedly connected to the return path side plates 62, and this therefore would thrust the mounting structure 14 in the opposite direction.

However, as this is happening, the interconnecting positioning and force transmitting section 18, (called mostly the "interconnecting section 18" in this text), in the form of the interconnecting frame portions 104 are being moved from the neutral position with the cross arms 112 resisting this movement. Since these cross arms 112 are made of a resilient material, there is a spring action by which they are resisting the relative movement of the mounting structure 14 and the inertial structure 16 away from the neutral position.

Then when the current in the coils 58 is reversed, the field created by the coils 58 would exert a force to move the inertial structure 16 and the mounting structure 12 back toward their neutral position relative to one another. Also, the spring action of the cross arms 112 would exert a force to move the mounting structure 14 and the inertial structure 16 back to the neutral position.

Thus, it is apparent the inertial section 16 and the mounting section, coupled with the spring action of the cross members 112 form a spring mass system which would have a resonant frequency. Assuming that the resonant frequency of this spring mass system is approximately the same as (or close to being the same as) the frequency of the amplified audio signal the action of this spring mass system would reinforce the forces created by the drive section 22 made up of the coil section 24 and the magnet 26.

The resultant force of the relative back and forth movement of the inertial structure 16 and the mounting structure 14 is reacted into the panel 33 of the seat of the chair 12. Thus, the panel 34 of the chair 12 will have a back and forth movement along with the housing 20 and the other components of the inertial section, and this results in the tactile wave traveling through the structure of the chair 12.

To discuss another feature of this embodiment of the present invention, as indicated earlier in this text, there are first and second mass selectable brass tuning blocks 76 and 78. By adding or subtracting mass from these tuning blocks 76 and 78, the resonant frequency of the spring mass system can be changed. This could produce benefits in various ways. For example, if the apparatus 10 were used in a specific piece of furniture, such as a chair, the panel or other structure to which the apparatus 10 is mounted may have certain characteristics relative to its mass, resistance to its movement, degree of resilience, etc. This may affect the resisting force provided by the chair or other object to which the apparatus 10 is mounted. Therefore, an adjustment could be made in the mass of these tuning blocks 76 and 78, to optimize the interaction of these components.

2) A Second Embodiment

A second embodiment of an acoustic wave generating apparatus 210 of the present invention will now be described with reference to FIGS. 9 through 15. Reference will first be made to FIG. 9, which is a cross sectional view taken transversely across a midsection of this apparatus 210 of the first embodiment.

In this second embodiment of the apparatus **210**, there is a mounting section **212** and an inertial section **214**, which is positioned in a chamber **215** of the mounting section **212**. These sections **212** and **214** are operatively connected to one another by an interconnecting positioning and force transmitting section **216** in a manner that the inertial section **214** reciprocates relative to the mounting section **212** in the chamber **215**. (For convenience, as in the description of the first embodiment, in the following text the interconnecting positioning and force transmitting section **216** will simply be referred to as the interconnecting section **216**).

As in the first embodiment, the relative reciprocating movements of the sections **212** and **214** is accomplished by means of a drive section **218** which comprises two main components, namely a coil section **220** that is mounted in the mounting section **212**, and a magnet section **222** which is a major part of the inertial section **214**. To facilitate the description of this first embodiment, the apparatus **210** will be considered as having a longitudinal axis **224** (FIG. **10**), a transverse axis **226** (FIG. **10**) perpendicular to the longitudinal axis, and a vertical axis **228** which is perpendicular to both the longitudinal axis **224** and the transverse axis **226** (FIG. **9**).

As in the description of the first embodiment, the terms “upper” and “lower” shall be used in this text for convenience of description, and in actual practice, the apparatus **210** could be positioned in different orientations such as an inverted orientation, a lateral orientation, etc.

With further reference made to FIG. **9**. It can be seen that in cross section the mounting section **212** has what is more of an hour glass configuration, and is made up of three sections, namely, upper and lower sections **230** and **232** of a greater width dimension, and a middle section **234** having a lesser width dimension. The upper and lower sections **230** and **232** are or may be identical (or substantially identical) to one another, so the following description of the upper section **230** is meant to apply as well to the lower section **232**.

The upper section **230** of the mounting section **212** has a top plate **236** which has an overall rectangular configuration and two rectangular side plates **238** extending downwardly from lateral outside edges of the upper plate **236**. The lower edges of the side plates **236** each connect to inwardly and downwardly sloping transition plate sections **240**. The lower section **230** of the mounting section **212** likewise has the bottom plate **236**, the side plates **238** and the upwardly and inwardly extending transition plate sections **240**, so that the lower section **232** is a mirror image of the upper section **230**.

The middle section **234** of the mounting section **212** comprises two rectangular intermediate side plates **242** having upper and lower edge portions which join to, respectively, the lower edge portions of the upper transition plate sections **240** and to the upper edges of the lower transition plate sections **240**. Also, the sidewalls **242** of the middle section **234** may have a plurality of laterally and outwardly extending ribs **244** which can function as heat dissipating members or fins. Also, these ribs **244** have the benefit of adding structural strength and stiffness.

As in the first embodiment, the three sections **230**, **232** and **234** of the mounting section **212** can be made of metal, plastic or some other material as a rigid unitary structure, such as being made by being machined, molded, extruded or cast and/or made of components welded or otherwise joined to one another. In FIG. **15**, the mounting structure **212** is shown in an isometric view, and there is shown an end plate **246** which can be joined to an open end portion of the mounting structure **212**. While not shown in FIG. **15**, a similar end plate **246** would be connected to the opposite end of the mounting section **212**.

The two end plates **246** each have a mounting flange **248** at right angles to the end plate **246**, and the mounting flanges **248** can be used to form the section **212** to a bottom panel of a chair such as that shown in FIG. **1**. The flanges **248** can be provided with openings **250** by which this connection can be made. Also, the two end plates **246** are shown provided with four corner located openings **252** to match with corner openings **254** of the mounting sections **212** so that the end plates **246** can be joined to the end portions of the mounting structure **212** by screws, bolts or other connectors.

The aforementioned coil section **218** is made up of two coils **256** (see FIGS. **10** and **11**), of the coil section with each coil **256** being mounted to the interior surface of one of two rectangular magnetically permeable return plates **258** that are in turn connected to the interior surfaces of the side plates **242** of the middle section **234** of the mounting section **212**. The two coils **256** are (or may be) identical and each has a “race-track” configuration, where there are upper and lower intermediate straight longitudinally aligned coil sections **260** and **262** respectively, with the end portions of these two sections **260** and **262** being connected by oppositely positioned **180** degree curved end coil portions **264**. Each of these coils **256** has multiple windings, and each winding could be made in the form of a flat ribbon of an electrically conductive material which is coated by a suitable insulating material that is wound in layers to form the “racetrack”.

The aforementioned magnet section **222** comprises a rectangularly shaped magnet **266** and upper and lower pole plates **268** and **270**, respectively, fixedly connected to the upper and lower surfaces of the magnet **266**. As can be seen in FIG. **10**, the lengthwise dimension (the dimension along the longitudinal axis **224**) of the magnet **266** and the pole pieces **268** and **270** are the same, and the transversely and vertically aligned end surface portions **272** of the magnet **266** with its pole plates **268** and **270** terminate a short distance inwardly from the location **273** at which the end curved coil portions **264** of the two coils **256** join integrally to the upper and lower straight coil sections **260** and **262**. Also, as can be seen in FIG. **9**, the lateral outside edges **274** of the two pole plates **268** and **270** are positioned a short distance beyond the lateral flat surfaces **276** of the magnet **266** to form the upper and lower flux gaps **278** at which the upper and lower longitudinally aligned coil sections **260** and **262** are located.

As can be seen in FIG. **9**, the magnet section **222** is in a neutral center position so that the two pole plates **268** and **270** are positioned at the mid height of, respectively, the upper and lower intermediate straight coil sections **260** and **262**.

The aforementioned interconnecting positioning and force transmitting section (now referred to as the “interconnecting section **216**”) comprises upper and lower interconnecting subsections **279**. These upper and lower subsections **279** are (or may be) identical (or substantially identical), except for being mirror images of one another. Accordingly, the following description of the upper subsection **279** is intended to apply to the lower subsection **279**.

Each of these interconnecting subsections **279** comprises a magnet interconnecting section **280** and an interconnecting frame section **282**.

Each magnet interconnecting section **280** comprises a magnet connecting plate **284** (see FIG. **9**) which is positioned against and connected to the upper surface of the upper and lower pole plates **268** and **270** respectively. Each magnet interconnecting section **280** further comprises a frame connecting plate **286** (see FIG. **9**) which is spaced upwardly (or downwardly for the lower magnet interconnection section **280**) from its related magnet connecting plate **284**. There is a pair of connecting posts **287** (see FIG. **9**) for each magnet

11

interconnecting section 280, and these are spaced at opposite end locations of each pair of the magnet connecting plate 284 and frame connecting plate 286.

The interconnecting frame section 282 is mounted into the mounting structure 212 at a location which is near to the connection of the side plates 238 with the upper (lower) transition plate sections 240. There is a downwardly facing shoulder 288 which extends longitudinally at a location spaced moderately below the perimeter portion of the upper and lower plates 36 (see FIG. 9).

Each interconnecting frame section 282 (See FIG. 12) comprises a mounting structure connecting frame portion 290, a magnet connecting frame portion 292, and an interconnecting frame portion 294. The mounting structure connecting frame portion 290 is in the form of a perimeter frame having opposite end portions 296 and side portions 298. The magnet interconnecting frame portions each comprise a longitudinally extended and centrally located elongate connecting plate 300 having a rectangular configuration, and having longitudinally spaced connecting locations shown herein as connecting openings 301 (see FIG. 12) by which a fastener (e.g. a bolt, a screw, etc.) can be made to an upper end of the aforementioned connecting post 288.

The frame interconnecting portion 294 functions as a resilient connection between the mounting section connecting frame portion 290 and the magnet connecting frame portion 292. In this second embodiment, this frame interconnecting portion 204 comprises transversely aligned pairs 302 of connecting arms 304, with each arm having an interconnecting end 306 by which it connects to the magnet interconnection frame portion 292, and an outer end 308 connecting to a related side portion 298 of the perimeter frame interconnecting portion 290. In the plan view of FIG. 12, it can be seen that there are five pairs 302 of the connecting arms 304, being positioned at evenly spaced longitudinally intervals along a major portion of the length of the interconnecting frame 282. In this particular arrangement, the two end portions 296 of the mounting section connecting frame portion 290 are spaced only a very short distance from the two end pairs 302 of connecting arms 304, and as shown in the drawings, there are an additional three pairs 302 connecting arms 304 positioned at the evenly spaced intervals between the two outermost pairs 302. The interconnecting frame section 294 may be made as a single integral structure so that both of the connecting end of the arms 304 have what can be termed as a cantilever connection, so that the arms 304 functions as cantilever beams that are fixedly connected at opposite end portions.

3) Various Arrangements of the Interconnecting Positioning and Force Transmitting Section

FIGS. 13 and 14 show two different arrangements of the interconnecting frame portion 294. The version shown in FIG. 13 is the version which is shown in FIG. 9. In FIG. 13, three of the pairs 302 of connecting arms 304 have both connecting arms 304 in a moderate curved configuration so that three of these pairs of arms 304 are curved to be above a plane occupied by the interconnecting frame 282. The other two pairs 302 of connecting arms 304 curve in a downward curve that extends below the plane occupied by the interconnecting frame 282. Thus, as can be seen in FIG. 13, circled numerical designations are given to each pair 302 of arms 304, beginning with the numeral one at the lower left end of FIG. 13 and continuing on through to the upper right end, as seen in FIG. 13. Three of the pairs are identified by circled numerals 1, 3 and 5, and these have an upwardly curved configuration, while those two pairs of 302 of arms 304 at a

12

location between pairs 1 and 3, and at a location between 3 and 5, respectively, designated by circled numerals 2 and 4 are in a downwardly curved configuration.

These arms 304 are resilient, so that when the magnet interconnecting frame portion 292 is deflected either upwardly or downwardly, these arms 304 function collectively as a balanced spring to maintain the alignment of the magnet section constant and to return the magnet interconnecting frame portion back toward its middle neutral location, as shown in FIG. 9. It will be noted that the spacing of the connecting arms 304 and also the alternating pattern of having the upwardly and downwardly curved arms 304 result in a symmetrical and balanced configuration, so that the interconnecting section 216 is able to reliably position the inertial section 214 so that its alignment orientation is substantially constant, and also so that its resisting force against upward and downward movement acts as a restoring force having a consistent pattern.

FIG. 14 shows an alternative configuration of the interconnecting frame section 282, and components of this alternative configuration will be given like numerical designations relative to the configuration of FIG. 13 with an "a" distinguishing those of this second arrangement.

In this second arrangement, the mounting structure connecting frame portion 290a is substantially the same as the mounting section connecting frame portion 290 of the first arrangement of FIG. 13, and also the magnet connecting frame portion 292 is the same as in FIG. 13. However, this alternative arrangement of FIG. 14 has the interconnecting frame portion 294a formed somewhat differently in that instead of having the curved arms 304 of the first arrangement of FIG. 13, the arms 304a of this alternative arrangement has each of the arms 304a in a straight line configuration, with these being in alignment with the plane occupied by the interconnecting frame 282a. However, the arrangement and spacing of these arms 304a and also the other components of this arrangement of FIG. 14 remain substantially the same so that the inertial section 214 is properly positioned not only in the neutral position, but also when it is moved upwardly and downwardly relative to the mounting structure 212.

It is believed that the mode of operation of this second embodiment is sufficiently clear from a review of the earlier text describing the operation of the first embodiment. Accordingly, the description of the operation of the second embodiment will not be included in this text.

A third arrangement of the mounting structure connecting frame portion 290 of this second embodiment is shown in FIG. 16. This third arrangement of FIG. 16 which has components which are the same as, or similar to, components of the earlier two arrangements 290 and 290a will be given light numerical designations, with a "b" suffix distinguishing those of this third arrangement.

In this third arrangement of FIG. 16, the components which are similar to, or substantially the same as, components of the earlier two arrangements are the magnet interconnecting plate 284b, the interconnecting frame section 282b, the mounting structure connecting frame portion 290b, and the magnet connecting frame portion 292b.

This third arrangement 282b differs in that instead of using the laterally extending arms 384a, there is provided an arrangement where there is on each side of the center magnet connecting frame portion 292b three triangularly shaped bracing members 306b, each of which comprises two laterally extending and slanted arms 308b. Each pair of arms 308b meet at a center location adjacent to the magnet connecting frame portion 292b, and extend from that juncture location

310b laterally in a diverging pattern to connect at the connecting locations **312b** at the mounting structure connecting frame portion **290b**.

In this particular configuration, the two arms **308b** of each bracing member **306b** form a triangle which in this particular embodiment has a configuration of an equilateral triangle. Each of these arms **308b** have a horizontal width dimension which is substantially greater than its depth dimension so that these can be resilient in an up and down motion, but would restrain any movement parallel to the longitudinal axis or the transverse axis.

The cross members and/or bracing members have a substantial transverse alignment component, and the overall alignment may vary somewhat from a totally transverse alignment.

4) Various Features and Aspects of the Design of the Embodiments

With the several embodiments and variations of the same now having been described, we will proceed to a discussion of various features and aspects of the embodiments of the present invention, with reference being made primarily to the first embodiment of FIGS. 2 through 8.

One significant aspect in the design of the tactile wave apparatus **10** relates to bandwidth, which can be characterized as resultant force versus frequency. It is desirable that the apparatus exhibit a more balanced ratio of peak force to average force. One reason for this is that music signals typically consist of multiple instruments all playing at once, producing notes at different frequencies. Also the tactile wave generated at a base frequency of, for example, forty to forty-five Hz, has overtones at higher frequencies. A poor ratio of peak to average level, (i.e., a high peak force but low energy at other frequencies) will accentuate a single instrument or the base frequency rather than provide a more balanced response to all of the instruments.

A key factor in what can be called a balanced transducer design is optimizing the driving force to the moving mass ratio. The bandwidth is proportional to the ratio of the driving force to the moving mass. Although reducing the magnitude of the moving mass will further increase bandwidth, the moving mass is also critical with respect to the resultant vibration force transmitted or "applied" to the listener.

To discuss briefly some of the physical principles involved, the resultant force applied to the listener defines the basic principle of operation. The transducer operates in accordance with Newton's 3rd law. Simply stated, "to every action there is always imposed an equal reaction". Or, $F = -F$ where F is an action force and $-F$ is the reaction force. This expression, $F = -F$ can also be stated in terms of Newton's 2nd law (in algebraic form, $F = ma$, where F is a force that produces an acceleration, " a " is the mass " m ". The acceleration " a " is proportional to the applied force and the constant of proportionality is the mass, " m ")

Newton's 3rd law can then be restated as $m_1 a_1 = M_2 A_2$. In the specific case of the transducer, m_1 is the mass of the permanent magnet structure assembly (the moving mass) and a_1 is the acceleration of the permanent magnet structure assembly. M_2 is the mass of the transducer chassis and the mass of the structure the transducer or shaker is attached to. (e.g., a chair or car seat, etc.). A_2 is the resultant acceleration of the shaker structure and attached mass. The product of the acceleration, A_2 and the moving mass, M_2 is the vibration or stimulus transmitted to the "listener".

As indicated above, the bandwidth is inversely proportional to the magnitude of the moving mass and directly

proportional to the driving force. The relationship of the moving mass to both applied force (to the listener) and bandwidth requires an optimization of the mass. Too much mass will increase the force applied to the listener but at the expense of bandwidth. Too little mass will increase the bandwidth but at the expense of applied force. Thus, if the inertial mass is made smaller and the driving force remains the same, the bandwidth increases. Then if in addition to the making the inertial mass smaller, if the driving force is increased this would further enhance the performance of the apparatus relative to the bandwidth.

Another consideration is that the driver section **22** (comprising the coil section **24** and the magnet section **26**) should be made to operate as efficiently as possible which would in turn mean that the amount of electric current generated would be as small as possible and yet be able to generate the desired level of force. As it turns out, optimizing the design to increase efficiency also relates to optimizing the bandwidth of the apparatus **10**. The force generated by the drive section **22** is directly proportional to the flux density at the flux gap, and the flux density is greater if the width of the flux gap is made smaller.

Also, if the flux density is increased, for the coil to generate the same force on the inertial mass, then the electric current passing through the coil could be reduced by a corresponding amount to generate this same force level since the force is related to flux density times the magnitude of the current. Since the heat loss of an electric current is proportional to the square of the magnitude of the current, if the amount of the current is reduced by, for example, to one-half, the heat losses would be decreased by four times.

However, if the width of flux gap is to be made smaller, this necessitates that a number of design parameters should be considered. In this first embodiment, the coils **58** remain stationary, and the magnet section **26** moves upwardly and downwardly in the flux gaps **94**. If the width of these flux gaps **94** are to be decreased, then the coil sections **64** and **66** would be that much closer to the side edge surfaces of the pole plates **72** and **74**. In order to avoid the pole plates **72** and **74** from coming into contact with the coils **64** and **66** during this up and down movement of the magnet section **26** must be controlled to remain within rather close tolerances.

On the other hand, it was indicated above that if the length of the path of travel of the inertial mass at a given power input is to be made as large as is practical to obtain the desired bandwidth. This adds to the problem of how to keep the movement of the magnet section **26** within very close tolerances. If there is any wobbling or departure of the magnet section **26** from the vertical path of travel, this would require the wider flux gap.

Certain features of the design the embodiments of the invention are related to this consideration, and these will now be discussed relative to the first embodiment of FIGS. 2-8. In the apparatus **10** of this first embodiment, the two coils **58** are identical to one another and each coil **58** is symmetrical with respect to the longitudinal, transverse and vertical axes **28**, **30** and **32**. The substantially linear coils sections **64** and **66** of each coil **58** are parallel to one another and lie in the same vertically and longitudinally extending plane passing through the center of the coil. Further, the upper linear coil sections **66** of the two coils **58** lie in the same horizontal plane, and the lower linear coil sections **66** also lie in the same horizontal plane.

The upper and lower side surface portions **92** of the upper and lower pole plates **72** and **74** are all parallel with one another. The two side surface portions **92** on one side of the pole plate **72** lie in the same longitudinally and vertically

15

aligned plane, and the two side surface portions 92 on the opposite side also lie in the same vertically and longitudinally aligned plane. The centerline of two upper side surface portions 92 lie in the same horizontal plane, as do the two lower side surface portions 92.

Thus, with this arrangement of the coils 58 and the side surface portions 92 the pole plates 72 and 74, when the identical amplified signals are passed through the two coils 58, the forces transmitted into the magnet section 26 are symmetrical and extend along substantially the total length of the side surface portions 92 of the pole plates 72 and 74 and also along the linear coil portions 64 and 66. Thus, the distribution of these forces along those lengths contributes to the stability of the magnet section 26 in moving within very close tolerances along the vertical axis with very little deviation with regard to any rotational movement about any of three axes of the longitudinal, transverse and vertical axes.

As indicated previously, the interconnecting and positioning section 18 comprises upper and lower frames 104. Each frame 104 is symmetrical about both the longitudinal axis 106 and the transverse axis 107. Thus, the two longitudinally extending edge members 108 have the same physical configuration and are spaced equally from the longitudinal axis 106 of that frame 104. Each of these edge members 104 is connected to the housing 20 to limit any lateral movement, this being accomplished in that particular embodiment by the flange 114 and slot 116 connection.

The cross members 112 are constructed with a relatively greater width dimension than thickness dimension. Thus, these cross members 112 provide substantial resistance to any relative movement of the magnet connecting member 110 along the longitudinal axis 106. Yet the thickness dimension of the cross members 112 is small enough, so that (with the cross members 112 being a resilient material) the cross members 112 permit the up and down movement of the center section 110 within very close tolerances relative to any deviation from the vertical path of travel.

Thus, with the two frame members 104 being identical with one another, and with the cross members 112 being symmetrical, the movement of the magnet section 26 is restrained to be along the vertical axis, and rotational movement about any of the three axes 28, 30 and 32, is restrained. Thus, with symmetrical forces being applied both by the drive section 22 and the interconnecting and positioning section 18, and with the geometry of the magnet section 26 being symmetrical, the movement of the magnet section 26 in its up and down path is tightly constrained to be within quite close tolerances.

5) Relationships of Design Parameters of the Embodiments

a) Introduction

With the foregoing being given as further background information, let us turn our attention now to yet more of the design parameters of the apparatus 10.

In order to discuss further the design features of the embodiments of the present invention, reference will now be made to FIG. 17. It can readily be seen that FIG. 17 is identical to FIG. 2, which shows the first embodiment which is a later design of an embodiment of the invention. However, for purposes of leaving the drawing of FIG. 17 uncluttered for the discussion which is to follow, the numerical designations in FIG. 17 have been omitted.

In FIG. 17 there are indicated nine dimensions which are labeled "a" through to "i". These dimensions will be discussed one at a time in the following nine paragraphs, starting

16

out with dimension "a", then dimension "b", etc. down to dimension "i". Since the magnet 70 is not shown in either FIGS. 2 or 17, the length dimension of the magnet 70 has simply been given a letter designation "m".

In an actual apparatus that has been designed and constructed in accordance with FIGS. 2-8, the length dimension of the magnet 70 is four inches. This four inch dimension of the magnet 70 will be considered to be a reference dimension, and each of the dimensions "a" through "i" will be given a percentage value which is calculated in accordance with the four inch length dimension of the magnet 70. The magnet dimension is deemed to be 100%, and the other dimensions will be given a percentage value which is calculated in accordance with the four inch dimension of the magnet 70. Thus the dimension "f" which is 1.8 inches has a percentage value of 45%, since 1.8 is 45% of 4.0 length of the magnet which is at 100%.

There will now be in the following nine paragraphs a short presentation of each of these dimensions "a" through "i".

- a) This dimension "a" is about 88.5%, and this is the total width dimension (i.e., transverse dimension) of the housing 20.
- b) The dimension "b" is the vertical dimension of the housing 20, and this is at about 68% value.
- c) The dimension "c" is the transverse dimension of each of interconnecting subsections which is distance between (connecting frames) 104, and is at about 82%.
- d) The dimension "d" is the transverse dimension of the drive section 22, (i.e., width dimension) which is measured from the outside surfaces of the return plates 62. Thus this drive section 22 comprises the return plates 62, the coils 58, and the magnet section 26. The percentage value of this dimension "d" is about 23%.
- e) The dimension "e" is the effective width dimension of the magnet section 26, which is deemed to be the distance between the outside edge surfaces of each of the pole plates of 72 and 74, since these are the outer location at which the electromatic forces are imposed on the magnet section 26. This dimension "e" is about 12.5%.
- f) The dimension "f" is the vertical spacing distance of the upper and lower interconnecting subsections 104. This dimension is about 45%.
- g) This dimension "g" is the effective vertical dimension of the magnet section 26 (i.e., the magnet 70 with the pole plates 72 and 74). This is measured from the vertical center locations of the pole plates 72 and 74, and the reason for this is that this would be the vertical center location where the forces between the pole plates 72 and 74 and the middle coil sections 64 and 66 are applied. This effective vertical dimension is at about 23%.
- h) This dimension "h" is the transverse distance between the outer edge surface of the two base flanges 144 which are actually extension of the lower plate 42 of the mounting section 14, with these flanges 144 being the location of which the mounting section 14 is secured to the seat platform 34 or other structure. The percentage value is about 107%.
- i) The dimension "i" is the transverse distance between the outer surfaces of the two plates of the middle portion of the housing 20. This has a percentage dimension of about 29%.

Finally, the magnet 70 has a length dimension "m" which does not appear on FIG. 17, and this length dimension is 100%.

Let us now examine some of these dimensional relationships regarding how they affect the function of the apparatus 10.

b) The Ratio of Dimension "c" to Dimension "e"

Dimension "c" is the transverse dimension of the interconnecting frames **104** and dimension "e" is the effective width of the magnet **70**, which are, respectively, 82% and 12.5%. This makes the ratio of 82% to 12.5% which translates to about 6.5 to 1. The magnet **70** along with the pole plates **72** and **74**, and also the tuning blocks **76** and **78** comprise a greater part of the inertial mass, and for the reasons indicated previously in this text, it is essential that this inertial mass move upwardly and downwardly within very close tolerances to the vertical path of travel of the magnet section **26**, and also stay properly aligned and centered on that vertical path of travel. These are in turn connected to the upper and lower centrally located magnet connecting members **110** of the frames **104**, and these are in turn attached to the cross members **112** that connect to the edge members **108**.

As the inertial mass moves upwardly and downwardly, this will cause a moderate bending of the cross members **112**. With this dimension "c" being made substantially greater than the width of the inertial mass, the up and down path of travel causes substantially no elongation along the length of these cross members **112**, which in this instance is almost infinitesimal. At the same, these cross members **112** have sufficient strength to maintain the magnet section **26** in its neutral position, and also (being resilient cross members) would provide the upward and downward forces to bring the magnet section **26** back to its central position. Present analysis indicates that if this dimension "c" were made substantially smaller, the design changes that would need to be made to maintain a given length travel would result in the magnitude of the tolerances of the vertical path of travel of the magnet section **26** being increased, and its capability of moving vertically within very close to tolerances would be diminished.

As indicated earlier in this text, since this enables the mid-coil sections **64** and **66** and the edge surface portions of the pole plates **72** and **74** to be positioned within very close to one another, this would increase flux density across the flux gaps. Thus, with the present design, the amount of current which would be required to produce a given level of force from the magnet section would be kept to a lower level, thus improving efficiency and reducing unwanted heat being generated.

Obviously, these dimensions could be varied for a variety of reasons, and this of course could change these relationships.

As indicated above, this ratio of "c" to "e" is 6.5 to 1. To discuss the variations that could be made in this ratio, we will first establish a "ratio difference value" by subtracting the value 1 from 6.5 to give a ratio difference value of 5.5 which represents the amount that dimension "c" exceeds dimension "e". This value 5.5 could be decreased by increments of 0.5 toward an intermediate level of 4, which would reduce the ratio toward 5 to 1, or further in 0.5 increments toward a level of 2 to a value of 3 to 1. Or the value of 5.5 could be increased by 0.5 increments of 0.5 up to 7.0 which effectively would make the ratio 8 to 1 or toward a higher value of 11 for a 12 to 1 ratio.

If this ratio is made greater up to, for example 12 to 1, there would have to be either a substantial increase in the dimension "c" and/or a substantial decrease in the width of the magnet section. Present analysis indicates that for most practical situations, this ratio would not be increased or decreased to the limits given above. However, there may be some other design requirements that would dictate such departures even further from the 6.5 to 1 ratio.

c) The Ratio of Dimension "c" to Dimension "g"

This dimensional relationship is closely related to the dimensional relationship of the dimension "c" to the dimension "e", and this ratio of the dimension "c" which (as indicated above) is the transverse dimension of each of the frames **104** to the dimension "g" which is the vertical dimension of the magnet section **26**.

With the percentage transverse dimension of the frame sections **104** (dimension "c") being 82%, and the vertical dimension "g" of the magnet section **26** having a percentage value of 23%, there is a ratio of 82% to 23%, which is about a 3.6 to 1 ratio. The relationship between the vertical dimension "g" of the magnet section **26** and the width dimension of the magnet section **26** is to a large extent dictated by the design requirements of the apparatus **10**. It is desired to make the apparatus **10** as compact as possible, and the magnet section **26** should have its width and height dimensions selected so that the mass of the magnet section is at the proper magnitude. Further, the magnet section **26** should be designed and dimensioned so that it could function properly as part of the drive section in generating the desired force to move the inertial mass. Therefore, the above comments made with respect to the ratio of dimension "c" to "e" would also apply to the ratio of dimension "c" to "g", with "g" being the vertical dimension of the magnet section **26**.

To discuss the possible changes in this ratio which is about 3.6 to 1, we shall also subtract the numeral 1 to obtain a ratio difference value which leaves 2.6 to 1. This 2.6 value could be decreased in increments of 0.2 first downwardly toward an intermediate level of 2, which would be a ratio of 3 to 1, or further downwardly 2 to 1 or possibly lower.

Or the value of 2.6 could be raised in increments of 0.2 toward an intermediate level of 4 to make a ratio of 5 to 1 or higher in increments of 0.2 toward a ratio of 7 to 1 or possibly higher.

As with the "c" to "e" ratio discussed immediately above, present analysis indicates that as the design would approach these more substantial increases or decreases to depart further from the more desired design parameters less desirable. However, there may be other design changes to make this practical.

d) The Ratio of Dimension "c" to Dimension "d"

Another ratio to be examined is that between the dimension "c" which is the transverse dimension of the frames **104** of the interconnecting section **18** and the dimension "d" which is the total width of the drive section measured to the outside surfaces of the return plate **62**. This ratio is about 3.6 to 1. It should also be noted that the side plates **48** of the middle section **40** of the mounting section **14** are in close physical contact with the two return plates **62** which in turn are positioned to be in contact with the coils **58**. Thus, the heat generated in the coils **58** have a heat sink into the soft steel return plates **62** to the side plates **48** of the housing **20**, and also into the other adjacent portions of the mounting section **14**.

Therefore, there is something of a "balancing act" in arriving at an optimized dimension "c", and also having the side walls **48** at the middle of the housing **20** positioned so as to be able to be in proper heat transfer with the coils **58**. Beyond this, as indicated above, is part of the "big picture" the total mass and also the total mass of the inertial section **16** and its transverse and vertical dimensions must be kept within practical design limits.

This ratio of "c" to "d", could be increased and decreased generally in the same way that was explained above with reference to the ratio "c" to "g" and "c" to "e". Thus, this would make this the ratio as high 10 to 1, or as low as possibly

3 to 1 or as low as 2 to 1 by increments of 0.2 or 0.5. The comments made above with reference to the ratio "c" to "g" would in large part also apply to the ratio of "c" to "d", and this would bring us to increases up to about as high as possibly 10 to 1 or higher, or as low as possibly 2 to 1.

e) the Ratio of Dimension "c" to Dimension "m"

The percentage values of "c" and "m" are 82% and 100% respectively, with the 82% dimension being the transverse width dimension of the positioning frames 104 and the dimension "m" being 100% and the length of the magnet 70. This ratio of 82 to 100 translates to 0.82 to 1.

We shall first discuss the situation where distance "m" remains the same relative to the other numerical design parameters given by the letters "a" through "i" (except for the dimension "c" for the transverse dimension of the frames 104). In this instance if the value of "c" is increased substantially, there would likely be an application of the law diminishing returns in that there would probably not be much benefit in doing so. However, there be some design changes or considerations which would make it otherwise.

On the other hand if this dimension "c" is substantially reduced, then the capability of the frames 104 may be somewhat diminished. Nevertheless, to allow for these situations, depending upon what other design changes are being made, the ratio of 0.82 to 1 could be increased or decreased in increments of 0.4 up toward as high as 1.5 to 1 or higher toward 2 to 1, or diminished by increments of 0.4 toward a level of 0.6 to 1, or possibly as low as 0.4 to 1 or possibly lower.

With regard to this ratio being changed by either increasing or decreasing the length of the magnet (i.e., dimension "m"), the various considerations relating to changing this dimension of the length of the magnet section 26 is discussed in more detail in section g which follows. The considerations discussed in that section would apply in large part to this present section e, so it will not be repeated at this point.

f) The Ratio of Dimension "c" to Dimension "f"

The ratio of "c" to "f" is 82 to 45 which turns out to be approximately 1.8 to 1. As indicated several times above, the dimension "c" having an 82% value is the transverse width of the frames 104 of the interconnecting section. The dimension "f" is the vertical spacing distance between these two frames 104, and it has a value of 45%. Thus, the 82% to 45% translates into a ratio of about 1.8 to 1.

We will assume that the value 1.8 of this ratio can be increased or decreased by increments of 0.2, so that it could increase, for example, to 2.0, 2.2, etc. If the dimension "c" is to remain constant along with the other dimensions "a" through "i", and the dimension "f" (which is the vertical spacing of the frames 104) were to be increased, this could reasonably be done to some extent for some design requirements, without detracting significantly to its value in properly centering the magnet section in its up and down travel. On the other hand, if this dimension is made smaller, this would permit the vertical dimension of the housing to be reduced, thus making the apparatus more compact.

While the analysis of the present design would indicate there may not be much value in making a significant amount of modification of this ratio, within the broader scope, it would be possible to increase the value of 1.8 by increments of 0.2 toward, for example, 2 to 1 or 3 to 1 or higher, or to decrease it by 0.2 increments down toward 1.2 to 1 or 0.8 to 1.

g) The Ratio of the Dimension "m" to the Dimension "e"

This is the ratio of the length of the magnet (dimension "m") to the transverse width dimension of the magnet section (dimension "e"). These percentage values are 100% to 12.5% so that the ratio between these is 8 to 1. This ratio could be changed by increasing the length of the magnet (i.e., dimen-

sion "m") so that this ratio could be at least a 10 to 1, 15 to 1, or at least in theory as high 20, 30 or 40 to 1 or higher), if that were the done, then the other components would have to be increased in length dimension by a comparable amount.

5 There may be some design applications where this may be a desired, such as increasing the inertial mass by increasing length "m" while keeping the same cross section of the magnet section 76. Thus, to accommodate the different design options, is it assumed that this ratio could be increased substantially.

10 On the other hand decreasing this ratio while the dimension "e" remains the same this would shorten the length of the magnet 70. However, any significant shortening of the length of the magnet 70 would reduce the force to move the magnet and its associated mass up and down, but there would be a corresponding reduction in the amount of the inertial mass assuming a constant cross section. However, this may reduce the ability of the magnet to be more stable with regarding to maintaining its orientation during the up and down movement.

20 As discussed earlier in this text, by distributing the force over a greater length dimension of the longitudinal axis, this enhances stability so that there can be closer tolerances in the flux gaps 94. Nevertheless, for various design reasons, it may be that the value 8 of the ratio of 8 to 1 be reduced to reduce the length of the magnet by increments of, for example, 1.0, we would arrive at a lower limit of 6 to 1, 4 to 1, 3 to 1 or possibly 2 to 1. However, present analysis indicates that not only would the mass be substantially reduced, but there would likely be greater difficulty in maintaining the up and down movement of the magnet within the sufficiently close tolerances.

h) The Ratio of the Dimension "a" to Dimension "b"

35 This is the relationship of the transverse width of the housing (dimension "a") and the vertical dimension "b" of the housing 20. The dimension "a" is at about 88.5% and the dimension "b" is about 68%. The ratio of 88.5 to 68 translates to about 1.3 to 1.

40 These two dimensions are dictated to a large extent by the transverse dimension of the frames 104, and the vertical dimension "e" of the magnet section 26, plus the added vertical dimensions that may occur due to the use of the tuning blocks 76 and 78. Nevertheless, since there may be different requirements due to modifications in the design, quite possibly the 1.3 value of this ratio could be modified by 0.1% increments up to a level of 1.8 to 1 or possibly 2 to 1 or 3 to 1, or reduced to a ratio of 1 to 1, or 0.8 to 1 or 0.6 to 1.

i) The Ratio of the Dimension "a" to the Dimension

50 The outside dimension of total width dimension "a" (i.e., transverse dimension) of the housing 20 is 88.5%, and the percentage transverse width dimension "i" between the outside surface of the middle portion of the housing 20 is 29%, so that there is a ratio of 88.5% to 29% which translates to a 3 to 1 ratio.

55 As indicated earlier in this text, each of the two return path plates 62 are positioned in contact with the coil section 58 and also with the middle housing plates 40 so that there is a heat sink from the coil 58 into the return path plate 62 and to the plates 40 of the housing 20. Accordingly, this dimension "i" is dictated primarily by the width dimension of the drive section 22 of the apparatus 10 and thus will be a small amount greater dimension "d". Thus, the dimension variations of the dimension "i" would be about one quarter greater than those of the dimension "d" of the drive section. The ratio of 3 to 1 could be lowered to 2.5 to 1 or 1.5 to 1, or increased possibly to 4 to 1 or 5 to 1.

It is evident that various modifications could be made to the present invention without departing from the basic teachings thereof, and that the descriptive text of these embodiments is not intended to define the scope of the present invention, since that is contained in the claims. Therefore, when the text of this patent application discloses particular components and configurations and arrangements of these components, this description is not intended to limit corresponding recitations of these components in the claims to that particular configuration or component.

Also, the various relationships of the design parameters of the embodiments as disclosed in the previous text are characteristic of the apparatus being designed for one application, and yet could be used in a variety of applications. Nevertheless, the design requirements may be rather different for different applications, such as operating in different environments, the need to have different frequency or frequencies and/or strength of the tactile waves being generated, dimensional requirements due to the configuration or characteristics of the structure or other device with which it is to be associated, etc. Thus, while some of these relationships may be applicable to these somewhat modified designs, it could be that others are not. Therefore, providing this information of these various design parameter is not necessarily to limit the scope of the claims in covering apparatus which may be totally outside of some of those relationships, and the scope of the claims is not intended to be limited to incorporating any or all of these design requirements, without departing from the basic teachings of the present invention.

The invention claimed is:

1. An apparatus adapted to transmit low frequency tactile waves into a structure and/or to a person's body, said apparatus comprising:

- a) a mounting section comprising at least a housing defining a chamber, said housing having a longitudinal axis, a transverse axis and a vertical axis;
- b) an inertial section comprising at least a generally longitudinally aligned magnet section mounted in said chamber for movement upwardly and downwardly from a neutral location, said magnet section having upper and lower pole portions, with each pole portion comprising oppositely positioned, generally longitudinally aligned pole side surface portions;
- c) a coil section comprising two laterally spaced coils mounted to said housing and located in said chamber on opposite sides of said magnet section, each coil having upper and lower generally longitudinally aligned coil portions and first and second end connecting coil portions connected between first and second end portions, respectively, of the generally longitudinally aligned coil portions, each generally longitudinally aligned coil portion being located next to a related one of said pole side surface portions when the magnet section is at its neutral position;
- d) an interconnecting section comprising upper and lower interconnecting subsections, said upper subsection having a first operative connection to said mounting section and a second operative connection to an upper portion of the inertial section, said lower subsection having a first operative connection to said mounting section and a second operative connection to a lower portion of said inertial section, said interconnecting section being constructed and arranged to permit vertical up and down movement of said magnet section as part of the inertial section and to restrict rotational movement of said magnet section about any of said longitudinal, transverse and vertical axes and restrict movement of said magnet section

tion in a direction having either or both of a transverse or a longitudinal alignment component so as to restrict movement of said magnet section to vertically aligned up and down movement, said interconnecting section being resiliently connected to said inertial section to locate said magnet section in the neutral position and to resiliently urge said magnet section toward the neutral position;

whereby when the coils are simultaneously energized with a signal, substantially uniform and equal electromagnetic forces are created along the length of the magnet section on opposite sides thereof to cause up and down cyclical movement of the magnet section as at least part of the inertial section, with the interconnecting section applying resilient forces to move the magnet section back toward its neutral position while maintaining consistent orientation of the magnet section and minimizing any deviation from vertically aligned up and down movement.

2. The apparatus of claim 1, wherein said coil section comprises two generally vertically aligned return path members which are located on opposite sides of the magnet section, each return path member being adjacent to, and extending between, the upper and lower generally longitudinally aligned coil portions of an adjacent one of the coils to form a flux path between the upper and lower generally longitudinally extending coil portions.

3. The apparatus of claim 1, wherein said inertial section is arranged to further comprise an upper and/or lower tuning member or members, with said magnet section and said tuning member of members each comprising at least part of said inertial section with the mass of said inertial section being centered relative to a vertical plane generally coincident with said longitudinal axis.

4. The apparatus of claim 1, wherein each of said interconnecting subsections comprises two oppositely located longitudinally extending housing connecting portions, a central longitudinally aligned connecting portion, and two interconnecting portions connecting to and extending between the central connecting portion and the housing connecting portions, said apparatus being arranged so that with the magnet section in its neutral position, the two housing connecting portions and the central connecting portion are located in substantially the same horizontal plane.

5. The apparatus of claim 1, wherein said housing comprises an upper housing section, a lower housing section, and a middle housing section, the upper and lower housing sections each having side walls spaced transversely from the longitudinal axis and from each other at a greater distance, and the middle housing section having side walls spaced transversely from the longitudinal axis and from each other by a lesser distance, the upper and lower interconnecting subsections being located in, respectively the upper and lower housing sections, and the magnet section, the coil section and the return path members being located in the middle housing section.

6. The apparatus as recited in claim 5, wherein said coil section further comprises two generally vertically aligned return path members which are located on opposite sides of the magnet section, each return path member being adjacent to, and extending between, the upper and lower generally longitudinally aligned coil portions of an adjacent one of the coils to form a flux path between the upper and lower generally longitudinally extending coil portions, each of said coils being in sufficiently close contact with its related return path member so as to be in heat exchange relationship with its return path member, said return path member being in sufficiently close contact with an adjacent one of the side walls of

23

the middle housing section so as to be in heat exchange relationship therewith, so that the path members and the side plates of the middle housing section function as a heat sink for the coils.

7. The apparatus of claim 2, wherein each of said interconnecting subsections comprises two oppositely located longitudinally extending housing connecting portions, a central longitudinally aligned inertial connecting portion, and two interconnecting portions connecting to and extending between the central connecting portion and the housing connecting portions, said intermediate connecting portions being structured with respect to one another to restrict any movement of the magnet section having longitudinal and/or transverse alignment components, but resiliently resist with substantially equal force vertical movement of the magnet section to properly position the magnet section within close tolerances in its upward and downward path of travel.

8. The apparatus as recited in claim 7, wherein each of said two interconnecting portions comprises a plurality of cross members which are spaced longitudinally from one another, and which connect between the central connecting portion and the two housing connecting portions, each of these cross members having a vertical thickness dimension which is sufficiently small to permit resilient up and down motion of the cross members, and a width dimension that is substantially greater than the depth dimension to resist any longitudinal or transverse movement of the cross members.

9. The apparatus as recited in claim 8, wherein at least some of said cross members have a rigid connection to either its related housing connecting portion or the central longitudinally aligned inertial connecting portion so that said at least some of said cross members function in a cantilevered manner in a resilient resisting up and down motion of the inertial section.

10. The apparatus as recited in claim 7, wherein each interconnecting subsection has its housing connecting portions and the central longitudinally aligned inertial connecting portion positioned in substantially the same horizontal plane.

11. A method of providing a low frequency tactile waves to be transferred into a structure and/or a person's body, said method comprising:

- a) providing a mounting section comprising at least a housing defining a chamber, said housing having a longitudinal axis, a transverse axis and a vertical axis;
- b) providing an inertial section comprising at least a generally longitudinally aligned magnet section and mounting said magnet section in said chamber for movement upwardly and downwardly from a neutral location, with said magnet section having upper and lower pole portions, and with each pole portion comprising oppositely positioned, generally longitudinally aligned pole side surface portions;
- c) providing a coil section comprising two laterally spaced coils, and mounting said coils in said housing on opposite sides of said magnet section, with each coil having upper and lower generally longitudinally aligned coil portions and first and second end connecting coil portions connected between first and second end portions,

24

respectively, of the generally longitudinally aligned coil portions, and positioning each generally longitudinally aligned coil portion so as to be located next to a related one of said pole side surface portions when the magnet section is at its neutral position;

d) interconnecting said inertial section to said mounting section by means of an interconnecting section comprising upper and lower interconnecting subsections, operatively connecting said upper subsection, by making a first operative connection to said mounting section and a second operative connection to an upper portion of the inertial section, operatively connecting said lower subsection by making a first operative connection to said mounting section and a second operative connection to a lower portion of said inertial section, with said interconnecting section being constructed and arranged to permit vertical up and down movement of said magnet section as part of the inertial section and to restrict rotational movement of said magnet section about any of said longitudinal, transverse and vertical axes and restrict movement of said magnet section in a direction having either or both of a transverse or a longitudinal alignment component so as to restrict movement of said magnet section to vertically aligned up and down movement, said interconnecting section being resiliently connected to said inertial section to locate said magnet section in the neutral position and to resiliently urge said magnet section toward the neutral position;

e) energizing the coils simultaneously to generate substantially uniform and equal electromagnetic forces along the length of the magnet section on opposite sides thereof to cause up and down cyclical movement of the magnet section as at least part of the inertial section, with the upper and lower interconnecting subsections applying resilient forces to move the magnet section back toward its neutral position while maintaining consistent orientation of the magnet section and minimizing any deviation from vertically aligned up and down movement.

12. The method of claim 11, wherein said method further comprises positioning vertically aligned return path members on opposite sides of the magnet section, so that each return path member is adjacent to, and extending between, the upper and lower generally longitudinally aligned coil portions of an adjacent one of the coils to form a flux path between the upper and lower generally longitudinally extending coil portions.

13. The method of claim 1, wherein said method further comprises providing each of the interconnecting subsections with two oppositely located longitudinally extending housing connecting portions, also providing a central longitudinally aligned connecting portion and two interconnecting portions connecting to and extending between the central connecting portion and the housing connecting portions, said method further comprising arranging the two housing connecting portions and the central connecting portion to be located in substantially the same horizontal plane when the magnet section is in its neutral position.

* * * * *