

# LEEMA

# SPLX

The Leema SPLX active subwoofers are ideal for stand alone use or as companions for the Leema Xen and Xyp loudspeakers, a combination that creates a phenomenally powerful and accurate system for music, home cinema and AV.

Available in two sizes, the SPLX 10 features a long excursion ten inch driver with ventilated voice coil, whilst the SPLX 12 utilises an ultra long throw twelve inch unit. Both variants are built around a massively powerful two hundred and fifty watt amplifier. The combination delivers power with stunning authority and ensures that headroom is never an issue.

Compact, high density, sealed cabinets of only 18 litres (SPLX 10) and 30 litres (SPLX 12) are employed to avoid the excessive group delay which characterises slow ported subwoofers, ensuring first class speed, rhythm and snap.

The unique pressure zone cabinet design allows the SPLX series to be used horizontally or vertically for maximum placement flexibility.

SPLX subwoofers deliver with precision and depth that belie the units' tiny dimensions. Bass extension, a hallmark of all Leema systems, reaches right to the lowest octave and beyond, with fine control and articulation. System integration is also exemplary.

A fully sweepable precision crossover filter and phase control allow matching with any system, while separate speaker and low level inputs cover any connection scenario. The filter section may be bypassed for AV use. Finally, fully automatic power-up and power-down ensure maximum user convenience.

The Leema SPLX is the obvious choice for those who put superb musical ability first but who also require power and control.

....Move your world



THE TRUTH IS HERE



ACOUSTICS

sunbury ♦ 7 holmisdale ♦ glendale

isle of skye ♦ Iv55 8wS

tel & fax: +44 (0)1470 511248

e-mail: sales@leema-acoustics.com

www.leema-acoustics.com

## Specifications

Useable In-Room Frequency Response

SPLX 10: 20Hz-500Hz SPLX 12: 18Hz-500Hz

Maximum SPL SPLX 10: >112dB SPLX 12: >115dB

Amplifier Power: 250 watts RMS into 4 ohms

Crossover Filter range: 40-160 Hz

Size SPLX 10 (h)x(w)x(d) in mm: 291 x 291 x 430

Size SPLX 12 (h)x(w)x(d) in mm: 370 x 370 x 460

Shipping Weights: SPLX 10 23Kg SPLX 12 28Kg

specifications subject to change without notice