



MODELO	Diametro	Pot. RMS	Fs hz	Qes	Qms	Qts	Vas - lts	Xmax	ηo -%	Sens 1W/m	Sd m²	Le	Re	BL -T.M	Ω
10SW 2	10"	180W	24.99	0.508	4.025	0.451	99.5	7.5mm	0.296	86.73	34.636	3.2mH	3.3	8.42	4Ω
12SW 2	12"	180W	23.80	0.592	4.024	0.516	190.0	7.5mm	0.419	88.24	53.093	3.2mH	3.3	8.85	4Ω
10SW 3	10"	300W	24.53	0.289	4.041	0.270	92.6	13mm	0.500	88.63	34.636	1.9mH*	2.4*	9.95	2x6Ω
12SW 3	12"	300W	23.40	0.347	3.908	0.318	175.5	13mm	0.631	90.02	53.093	1.9mH*	2.4*	10.36	2x6Ω
15SW3	15"	300W	23,01	0,566	4,377	0,501	365	13mm	0,76	91,01	80,425	1.9mH*	2,4*	10	2x6Ω
KW50.01	5"	50W	60.60	0.947	2.597	0.694	11.36	3mm	0.258	86.14	8.659	2.95mH	3.6	3.06	4Ω
KW65.01	6.5"	50W	63.00	1.057	2.328	0.727	13.71	3mm	0.320	87.07	12.272	2.95mH	3.6	3.65	4Ω

