

SPECIFICATIONS

MMA™ 875T Nine-Channel Modular Mixer Amplifier

SPECIFICATIONS

Output Power:
75 watts RMS

Power Bandwidth:
Direct: 20 - 20 K < 0.5% THD
XFMR: 50 - 20 K < 0.5% THD

Frequency Response:
Direct: 20 - 20 K \pm 1.0 dB
XFMR: 20 - 20 K \pm 3 dB

Total Harmonic Distortion:
0.02% at 1 kHz rated power

Output Regulation:
Direct: < 0.5 dB
XFMR: < 1.0 dB

Signal To Noise Ratio:
Master Volume Min: 95 dB
Master Volume Max: 77 dB
Power Amp Only: 95 dB

Tone Controls:
Bass: \pm 10 dB @ 100 Hz
Treble: \pm 10 dB @ 10 kHz

Contour:
+ 6 dB @ 100 Hz
+ 6 dB @ 10 kHz

Inputs:
Eight input ports, one dedicated
program input, bridge in/out

Input Sensitivity:

Ports 1-8: 100 mV @ 10 K ohms
PGM: 150 mV @ 10 K ohms
Bridge In/Out: 100 mV/3.3 K ohms

Preamp Out/Power Amp In

1.0 V @ 600 ohms/1.0 V @ 15 K ohms

Outputs:

Direct Out: 4 ohms
Fully Isolated XFMR: 8 ohms, 25 volts,
70 volts (100 V 220/240 Export)

Controls:

9 input gain controls, 1 bass control, 1
treble control, 1 contour switch, 1
master gain control, 1 power switch, 1
EQ defeat switch, 1 low-cut switch

Indicators:

Power LED (red), Activity LED (green),
SPS™ Active LED (yellow)

Protection:

Internal current limiting, SPS™
(speaker protection), output relays,
1 line fuse, and 2 internal fuses

Connectors:

Preamp out/power amp in, PGM input,
bridge in/out, RCA phono jacks
Ports 1-8: Card edge connector
Outputs: Screw terminals
Mute: Screw terminals
AC SJT, 3 prong

Power Consumption:

120 W, 60 Hz, 120 V AC Domestic
120 W, 50/60 Hz, 220/230-240 V AC
Export

Dimensions

3.5" H x 17" W x 15.5" D

Weight & Color:

26 lbs. Gray

Other Features:

Provisions for external master volume
control
Power output disconnected for 4
seconds after power on
Level-sensing muting at modular level

FEATURES

- 9 channel mixer/power amplifier system
- 20 - 20 kHz frequency response
- Bridging input/output
- Contour switch (special equalization)
- Bass and treble controls
- Preamp output/power amp input patch capability
- Short circuit and thermal protection
- SPS™ protection circuitry
- External volume control
- Built-in low cut filter (switchable from rear panel)
- Plug-in module capability
- Output impedance variations: 4 ohms, 8 ohms, 25 V and 70 V (100 V Export)
- Rack-mountable or stand alone package (Rack brackets are optional)
- Two mute lines

PEAVEY®
ARCHITECTURAL ACOUSTICS®

DESCRIPTION

The Architectural Acoustics MMA™ 875T is a high-quality mixer amplifier with nine separate input channels. Each channel provides a level control, and the master output section features bass and treble EQ controls (defeatable) and special equalization contour.

The MMA 875T provides unmatched application flexibility with an array of optional plug-in modules, allowing the system to be tailor-made for specialized installations. Input modules may be loaded-in as required for varying applications, number of input channels, special functions, etc.

The program input includes its own level control and is totally separate from the other eight channels. External signals may be patched in at this point as a system auxiliary input or the ninth input channel. Signals appearing at this input are routed directly to the master summing amplifier stage and are mixed with signals from the other eight channels. Systems requiring a single input may use the program input, but

the purchase of an input module is not necessary. The program level control regulates the level of this input, and the signal is routed through the system bass and treble controls.

The power section delivers 75 watts and includes built-in SPS™ protection, which allows the MMA 875T to produce full power capability without audible power amp clipping. A broad load impedance range is provided, and 25 and 70 volt fully isolated line outputs are standard equipment. The MMA 875T is packaged as a stand-alone unit, but will also rack-mount into a standard 19" rack with an optional rack-mount kit.

ARCHITECTURAL AND ENGINEERING SPECIFICATIONS

The mixer amplifier shall have eight modular input channels and one dedicated program input. The master section shall include one master volume level control, two EQ controls providing

10 dB of boost or cut at 100 Hz and 10 kHz, a "contour" switch providing 6 dB of boost at 100 Hz and 6 dB of boost at 10 kHz, and a green status LED. Internal muting shall be accomplished at the modular level by means of two dedicated mute lines. External muting shall be accomplished via screw terminals on the back panel. Provision for an external master volume control shall be made through barrier strip connections on the back panel.

The unit shall be packaged in a rugged metal chassis 17" wide by 3.5" high by 15.5" deep. The unit shall operate from 120 volts AC, 60 Hz power. The internal amplifier shall be capable of delivering 75 watts RMS into 4 ohms and 8 ohms, as well as providing 25 volt and 70 volt line outputs. The unit shall be capable of delivering rated power from 20 Hz to 20 kHz ±1 dB into 4 ohms at its direct output at less than 0.5% distortion with system hum and noise at least 77 dB below rated output. The unit shall be a Peavey Architectural Acoustics Division model MMA™ 875T.

LIMITED WARRANTY

Peavey Electronics Corporation warrants to the original purchaser of this new Architectural Acoustics product that it is free from defects in material and workmanship. If within one (1) year from date of purchase a properly installed product proves to be defective and Peavey is notified, Peavey will repair or replace it at no charge. (Note: Batteries and patch cords not covered.) "Original purchaser" means the customer for whom the product is originally installed.

Damage resulting from improper installation, interconnection of a unit or system of another manufacturer, accident or unreasonable use, neglect or any other cause not arising from defects in material and workmanship is not covered by this warranty. The warranty is valid only as to products purchased and installed in the United States and Canada.

THIS LIMITED WARRANTY IS IN LIEU OF ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE. UNDER NO CIRCUMSTANCES WILL PEAVEY BE LIABLE FOR ANY LOST PROFITS, LOST SAVINGS, INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PRODUCT, EVEN IF PEAVEY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. THIS LIMITED WARRANTY IS THE ONLY EXPRESSED WARRANTY ON THIS PRODUCT, AND NO OTHER STATEMENT, REPRESENTATION, WARRANTY, OR AGREEMENT BY ANY PERSON SHALL BE VALID OR BINDING UPON PEAVEY.

Peavey's liability to the original purchaser for damages for any cause whatsoever and regardless of the form of action is limited to the actual damages up to the greater of Five Hundred Dollars (\$500) or an amount equal to the purchase price of the product that caused the damage or that is the subject of or is directly related to the cause of action. This limitation of liability will not apply to claims for personal injury or damage to real property or tangible personal property allegedly caused by Peavey's negligence. For information on service under this warranty, call a Peavey customer service representative at (601) 483-5376.



Features and specifications subject to change without notice.

A Division of Peavey Electronics Corporation

711 A Street / Meridian, MS 39301 / U.S.A. / (601) 483-5376 / Fax 486-1278

#80302315

