

# HORN FOR PROFESSIONAL DRIVERS



## PH-2420

### SPECIFICATIONS:

- MATERIAL: A.B.S. with glass filled black polycarbonate
- COLOR: BLACK
- NOMINAL COVERAGE ANGLE (H X V)-6dB: 90° x 40°
- CUT OFF FREQUENCY ( HZ ) 600
- THROAT DIAMETER MM: 25 MM (1")
- MOUNTING TYPE: BOLT-ON

### MOUNTING DIMENSIONS:

- REAR HEIGHT MM : 164 mm (6.5")
- REAR WIDTH MM : 211 mm (8.3")

### OVER DIMENSIONS:

- MOUTH HEIGHT MM : 196 mm (7.7")
- MOUTH WIDTH MM : 242 mm (9.5")
- LENGTH MM : 135 mm (5.3")

- MOUNTING FLANGE THICKNESS MM : 6 mm (0.24")
- MOUNTING HOLES DIAMETER MM : 5 mm (0.2")
- MOUNTING HOLES NUMBER : 8

### BAFFLE CUT OUT MOUNTING:


- HEIGHT MM : 168 mm (6.6")
- WIDTH MM : 212 mm (8.3")
- NET WEIGHT : 0.42 kg (0.924 lb)
- SHIPPING WEIGHT : 0.67 kg (1.474 lb)

### PACKING CARTON DIMENSION:

- 260 mm x 220 mm x 155 mm
- 10.2" x 8.6" x 6.1"

### HORN RECOMMENDED DRIVERS:

- PA-D34, PA-D44, PA-D45, BM-D440, BM-D450, SD-450N, SN-D44, WN-D44



## PH-3220

### SPECIFICATIONS:

- MATERIAL: A.B.S. with glass filled black polycarbonate
- COLOR: BLACK
- NOMINAL COVERAGE ANGLE (H X V)-6dB: 100° x 60°
- CUT OFF FREQUENCY ( HZ ) 600
- THROAT DIAMETER MM: 25 MM (1")
- MOUNTING TYPE: BOLT-ON

### MOUNTING DIMENSIONS:

- REAR HEIGHT MM : 165 mm (6.5")
- REAR WIDTH MM : 260 mm (10.24")

### OVER DIMENSIONS:

- MOUTH HEIGHT MM : 198 mm (7.8")
- MOUTH WIDTH MM : 318 mm (12.5")
- LENGTH MM : 210 mm (8.27")

- MOUNTING FLANGE THICKNESS MM : 8 mm (0.315")
- MOUNTING HOLES DIAMETER MM : 6.35 mm (0.25")
- MOUNTING HOLES NUMBER : 8

### BAFFLE CUT OUT MOUNTING:

- HEIGHT MM : 170 mm (6.7")
- WIDTH MM : 266 mm (10.5")
- NET WEIGHT : 0.7 kg (1.54 lb)
- SHIPPING WEIGHT : 1.1 kg (2.42 lb)

### PACKING CARTON DIMENSION:

- 330 mm x 228 mm x 210 mm
- 13" x 9" x 8.3"

### HORN RECOMMENDED DRIVERS:

- PA-D34, PA-D44, PA-D45, BM-D440, BM-D450, SD-450N, SN-D44, WN-D44

