

Precision Devices 158

Re 5.77 Ω

Qms 14.91

Qes 0.25

Qts 0.24

Le 0.76 mH

L2 1.94 mH

R2 17.52 Ω

Vas 64.84 litres

Mms 85.23 g

Sd 855.3 cm²

Cms 107.33 $\mu\text{m/N}$

BL 25.39 T/m

Xmax 6 mm

Vd 0.529 litres

Ref. Efficiency 4.59 %

Nominal Diameter 380 mm / 15"

Voice Coil Diameter 101 mm / 4.0"

Available Impedances 4 Ohms/ 8 Ohms/ 16 Ohms

Power Rating 600 w (A.E.S.)

Peak Power (6dB Crest Factor) 2400 w (A.E.S.)

Sensitivity (1w - 1m) 98 dB

Frequency Range 40 Hz - 3 kHz

Recommended Enclosure Volume 60 - 200 Litres

Resonance 54.61 Hz

Voice Coil Winding Depth 19 mm / 0.75"

Magnet Gap Depth 11 mm / 0.43"

Flux Density 1.1 Tesla

Magnet Material Ceramic

Voice Coil Material Copper

Former Material Glass Fibre

Dust Dome Material Paper

Suspension Material Dual Fabric

Cone / Surround Material Paper / Fabric

Nett Weight 13 Kg / 28.66 lb.