



	Cursor 1	Cursor 2	Delta C2-C1
Frequency	100.009 kHz	10 Hz	-99.999 kHz
<b>Trace 1</b>	<b>Magnitude (dB)</b>	<b>Magnitude (dB)</b>	<b>Magnitude (dB)</b>
Measurement	3.586 dB	22.755 dB	19.169 dB
<b>Trace 2</b>	<b>Magnitude (dB)</b>	<b>Magnitude (dB)</b>	<b>Magnitude (dB)</b>
Measurement	-4.898 dB	-1.383 dB	3.515 dB

**Sweep**

Start frequency:	10 Hz
Stop frequency:	1 MHz
Center frequency:	500.005 kHz
Span:	999.99 kHz
Sweep mode:	Logarithmic
Numer of points:	201

**Hardware setup**

Device type:	Bode100R1
Serial number:	CK212C
Receiver bandwidth:	100 Hz
Output level:	-10 dBm
DUT settling time:	0 ms
Nominal Impedance:	50 Ω

**Calibration**

	Full-Range	User-Range
Gain	-	-
Impedance	-	-

**Termination**

	Channel 1	Channel 2
Gain	1 MΩ	1 MΩ
Impedance	1 MΩ	1 MΩ

**Attenuator setting**

	Channel 1	Channel 2
Transmission	10 dB	40 dB
Reflection	10 dB	10 dB

**Receiver switch**

	Channel 1	Channel 2
Gain	Internal	External
Impedance	Internal	Internal