COMPANY	SAMSON
TYPE CODE	
APPROVED DATE	03.6.23

APPLICANT	REVISED NUMBER AND DATE		
MP	1.	4.	7.
	2.	5.	8.
	3.	6.	9.

SIGN	DRAWN	CHECKED	APPROVED	NOTE
	LIMTRUST			

A-GND CHGND D-GND

SIZE	SHEET NO.
A2	

SCHEMATIC DIAGRAM

MODEL : S-500

CH1

4005187700
AMP B'D

CH2

4005187700
AMP B'D

4005181010 INPUT B'D

400518104O OUTPUT B'D

POWER B'D
4005181000

LED B'D
4005181020
CH1

LED B'D
4005181030
CH2

*SERVICE INFORMATION

1.RESISTANCE VALUES ARE INDICATED IN OHMS UNLESS OTHERWISE SPECIFIED. (K=1.000, M=1.000.000)
2.CAPACITANCE VALUES ARE SHOWN IN MICROFARADS UNLESS OTHERWISE NOTED. (P=MICRO-MICROFARADS)
3.ALL VOLTAGES ARE REFERED TO GROUND UNDER THE FOLLOWING CONDITIONS.
DC:NO SIGNAL EXCEPT WHERE INDICATED.
AC:RMS
4.-PRECAUTION-
A)ALL COMPONENTS ⚠ MARKED MUST BE REPLACED ONLY WITH ORIGINAL TYPE SPECIFIED BY THE MANUFACTURER. INTER M CORPORATION AND INSTALLED AS THE ORIGINAL SPACE AND POSITIONED AWAY FORM ADJACENT COMPONENTS WHERE APPLICABLE.
B)ALL SOLDERING MUST BE DONE IN A PROFESSIONAL MANNER USING SOLDER WHITE RESINE CORE ONLY.
C)ALL COVERS. SHIELD AND INSULATING SPACERS MUST BE REPLACED BEFORE RETURING APPLIANCE TO CUSTOMER.
D)A DAMAGE POWER SUPPLY CORD MUST BE REPLACED BEFORE RETURING TO CUSTOMER.
E)DIELECTRIC TEST CONSISTING OF 120V AC 60HZ IS TO BE APPLIED BETWEEN BOTH BALDES OF THE POWER SUPPLY CORD ATTACHMENT PLUG THE EXPOSE CONDUCTIVE SURFACE OF THE APPLIANCE FOR A PERIOD OF NOT LESS THAN ONE SECOND BEFORE RETURING APPLIANCE TO CUSTOMER.
F)THE ⚠ MARKED RESISTORS ARE MOUNTED THE P.C.B ON SLEEVES.