

# Amplieaux

AUDIO AMPLIFIERS BEYOND IMAGINATION



## SIMPELSTARK AX2

### WARMTH OF TUBES WITH NO TUBES

Delicate sound<sup>®</sup> approach of SIMPELSTARK AX2 involves an ultra linear symmetric topology with only 2 gain stages and very short signal path.

### ONLY DISTORTION NEGATIVE FEEDBACK

SIMPELSTARK AX2 has got no traditional global feedback loop, utilizing innovative ODNF approach with precise small signal error channel.

### SMART CONTROL/PROTECTION SYSTEM

Microcontroller based soft-start/protection system provides unprecedented reliability, taking care of both the amplifier & the speakers.



## NO COMPROMISE DESIGN

Dual mono configuration with separate power transformers and PSU modules for the left and right channels ensure very accurate soundstage.

High-power PSUs and proper wiring allow high output current capability when required.

Low noise and tube-alike harmonics profile make this amplifier particularly comfortable for long-time low-volume listening in the living room environment.

SIMPELSTARK AX2 especially shines playing acoustic music – classic, jazz, funk, soul, vocals.

Protection system utilizes solid state relays at the PSU rails as well as at the amplifier outputs, providing fast and reliable cut off in case protection system fires.

## SPECIFICATIONS

Output power	100W RMS @ 8 ohm
Frequency response	10Hz-150KHz ( $\pm 0.5\text{db}$ )
Input impedance	47 Kohm
Voltage gain	29db
Signal to noise ratio	117db (20Hz-20KHz)
THD 1KHz	$\leq 0.007\%$ (8 ohm)
THD 20KHz	$\leq 0.070\%$ (8 ohm)
IMD 14+15KHz	$\leq 0.007\%$ (8 ohm)
Power supply	230V AC (50Hz)
Net weight	24 kg
Protection shut down	DC offset ( $\pm 2\text{V DC}$ ) OPS Overcurrent OPS Overtemperature AC failure (mains)

**Amplieaux** is the trademark of **Virtual Zero Audio**  
New Hamburg, Ontario, Canada

<http://virtualzeroaudio.com/>

