

MPF920-Z

FEATURES AND BENEFITS

- Works with 720 kB and 1.44 MB floppy disks
- Standard 34 pin floppy interface for easy installation
- Mist white faceplate and eject button can be changed with matte black or granite colored parts (included) to match your computer
- High quality construction for years of reliable service

SPECIFICATIONS

PART NUMBER	MPF920-Z
DRIVE TYPE	Internal Floppy Disk Drive
DATA TRANSFER RATE (from disk)	500 kB/s max.
TRACKS	80
HEADS	2
ENCODING METHOD	MFM
ROTATIONAL SPEED	300 min-1
INTERFACE	34 pin floppy interface
CAPACITY	1.44 MB Formatted (2HD disk) 2 MB Unformatted (2HD disk)
MTBF*	30,000 POH
ENVIRONMENTAL	Operating Temperature 41° F - 125° F (5° C - 51.7° C) Humidity 8 - 80% RH (operating)
POWER VOLTAGE	DC 4.4 to 5.25V
SYSTEM REQUIREMENTS	IBM PC/AT Compatible PC Microsoft® Windows® 98/2000, Windows® XP Home & Professional, or Windows® Millennium Edition operating systems.
PACKAGE CONTENTS	Internal Disk Drive, matte black and granite colored faceplates and eject buttons, User's Guide
WARRANTY	One-year Limited

*MTBF specification is average based on normal office environmental conditions.
Actual experience may vary.

MEDIA COMPATIBILITY

MODEL	CONFIGURATION
MFD-2HD	1.44 MB High Density Floppy Disk

