

Power Amplifier

SRP-P50



- Offers a power output of 70W + 70W (4Ω load)
- Compact 1U-size body
- Toroidal transformer
- BTL connection
- Symmetrical circuit high supply voltage rejection ratio and stability
- Use of a coupling condenser made of silk fiber provides wide dynamic range
- Input level switchable between 0dBu and – 10dBu

Specifications

	SRP-P50	
Input Type	Balanced	Unbalanced
Input Impedance	more than 20kΩ	
Input Connector	XLR-3-31 type / Phono jack	
Operation	STEREO	MONO
Speaker Terminal	Screw type	
Rated Output Power	75W+75W(4Ω) 50W+50W(8Ω)	150W(8Ω)
Frequency Response	20Hz-20kHz +0dB/-0.5dB	
Input Sensitivity	0dBu/-10dBu selectable: 55W+55W(8Ω)	
T.H.D.	less than 0.05% (50W+50W) (8Ω) less than 0.1% (70W+70W) (4Ω)	less than 0.1% (150W, 8Ω)
Residual Noise Voltage	less than 120μ V.	less than 240μ V.
Operating Temperature	0 – +40 degree	
Stage Temperature	-20 – +60 degree	
Power Requirement	120V 60Hz	
Power Consumption	160W	
Mass	8kg (17 lb 10 oz)	
Dimensions	482 / 44 / 350 mm 19 x 1 ³ / ₄ x 13 ⁷ / ₈ inches	