

CABINET HARDWARE

Standard handle assembly
Casters with screws
Plastiglide feet
Metal feed thru washers
Metal front corners - 3 hole
Metal rear corners - 2 hole
SUNN name plate

71-0007
66-9459
58-1089
43-0061
62-0805
62-8053
73-0090

Service Data

All controls at maximum, Input signal .5V RMS, 2KHz

Scope Pic. No.	Point	Sensitivity
31	Pin 1 12AX7	20V/CM
32	Pin 6 12AX7	5V/CM
22	Pin 8 6AN8A	20V/CM
33	Pin 6 6AN8A	20V/CM
33	Pin 3 6AN8A	20V/CM
33	Pin 2 6AN8A	20V/CM
34	Pin 1 6AN8A	20V/CM

Volume control normal set			Notes
35	Output	20V/CM	Reverb max
36	Output	20V/CM	Vibrato max
28	Output	20V/CM	
40	Output	29V/CM	Mid boost on
All controls max			
37	Output	20V/CM	treble at minimum
38	Output	20V/CM	
39	Output	20V/CM	Bass at minimum

No signals input - All controls at maximum

Place screen over pre amp section

Maximum hum level reading

Scope Pic No 19

Reading at output

All readings taken with amp operating into 8 ohm dummy load

