



Vifa-Speak A/S
DK-6920 Videbæk
Denmark

Fabrikation af kvalitetshøjttalere
Production of Quality Loudspeakers


12" WOOFER

SPECIAL FEATURES:


- MAGNESIUM BASKET
- COATED PAPER CONE
- RUBBER SURROUND
- DOUBLE MAGNET SYSTEM
- LOW DISTORTION
- IDEAL FOR BASS REFLEX

NOMINAL IMPEDANCE	8 Ω
NOMINAL POWER (IEC 268-5)	100 W
MUSIC POWER (DIN 45500)	150 W
FREQUENCY RANGE	21-1000 Hz
SENSITIVITY (1W, 1m)	93 dB
EFFECTIVE CONE AREA	513 cm ²
VOICE COIL RESISTANCE	5,7 Ω
VOICE COIL INDUCTANCE	2,1 mH
OPERATING POWER	2 W
VOICE COIL DIAMETER	40 mm
VOICE COIL HEIGHT	14 mm
AIR GAP HEIGHT	6 mm
FREE AIR RESONANCE	21 Hz
MOVING MASS (incl. air)	53 g
FORCE FACTOR, B x l	12,7 Txm
MAGNET WEIGHT (49,2 oz)	1396 g
Qms	2,3
Qes	0,25
Qts	0,23
Vas	400 ltr

M30W0-49-08



Front



Rear

