



CPS CERTIFICATE

PRODUCT SEARCH

[MSDS](#)   [TDS](#)   [Products](#)   [Resources](#)   [About Us](#)   [News](#)   [Training](#)

## Automotive

>> Adhesives & Sealants

>> Appearance Products

>> Cleaners

>> Gasketing

Anaerobic Gasket Makers & Flange Sealants

Gasket Makers  
Gasket Removers

> Gasket Sealants

Specialty Gasket Maker

>> Hand Care

>> Lubricants

>> Maintenance & Performance

>> Specialized Maintenance & Repair

>> Thread Compounds

## Gasketing

Products > [Automotive](#) > [Gasketing](#) > [Gasket Sealants](#) > Permatex® High Tack™ Gasket Sealant



### Permatex® High Tack™ Gasket Sealant

Fast-drying all-purpose sealant dries to a highly tacky, non-brittle film. A reliable general adhesive. Remains effective under temperatures of -65°F to 500°F (-54°C to 260°C). Resists gasoline, oil, antifreeze, axle lube, kerosene, propane and butane. Level 3\*

**Suggested Applications:** Valve covers, fuel pumps, carburetors, manifold gaskets

Item #	Container Size	Pack	Part #	MSDS	TDS
80062	4 oz. brush-top can	12	98H		
80063	16 oz. brush-top can	12	98D		



Copyright © 2009 Permatex a division of Illinois Tool Works Inc. All rights reserved.  
 Permatex and ITW Performance Polymers & Fluids, Illinois Tool Works Companies.